

屋内照明器具特性	
品番 (品名)	L G W 8 5 0 3 6
光源	LDA4L-H-E17/S/4 x1 440.0lm
管理番号	K0123402(1)DB1
BZ分類	BZ10/0.9/BZ9

器具効率	44%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	20%		床	10%				10%				10%				10%				0%
下方光束	24%		室指数	照明率 (X0.01)																ZCM
保守率	良	0.63	0.6	1.9	1.3	0.9	0.7	1.7	1.2	0.9	0.6	1.4	1.0	0.7	0.5	1.1	0.8	0.6	0.4	0.2
	中	0.6	0.8	2.3	1.7	1.3	1.0	2.1	1.6	1.2	0.9	1.7	1.3	1.0	0.8	1.4	1.1	0.8	0.6	0.4
	否	0.56	1.0	2.5	2.0	1.6	1.3	2.3	1.8	1.4	1.2	1.9	1.5	1.2	1.0	1.5	1.2	1.0	0.8	0.5
			1.25	2.8	2.2	1.9	1.5	2.5	2.1	1.7	1.4	2.1	1.7	1.4	1.2	1.7	1.4	1.2	1.0	0.6
下方投影面積		cm ²	1.5	2.9	2.5	2.1	1.8	2.7	2.3	1.9	1.6	2.2	1.9	1.6	1.4	1.8	1.6	1.3	1.2	0.7
等価発光面積		cm ²	2.0	3.2	2.8	2.4	2.1	2.9	2.6	2.2	2.0	2.5	2.2	1.9	1.7	2.0	1.8	1.6	1.4	0.9
取付高さ	器具間隔最大限		2.5	3.4	3.0	2.7	2.4	3.1	2.8	2.5	2.2	2.6	2.3	2.1	1.9	2.1	1.9	1.8	1.6	1.1
	横方向 (A)	縦方向 (B)	3.0	3.5	3.1	2.8	2.6	3.2	2.9	2.6	2.4	2.7	2.5	2.3	2.1	2.3	2.1	1.9	1.7	1.2
Hm	0.00Hm	2.58Hm	4.0	3.7	3.4	3.1	2.9	3.4	3.1	2.9	2.7	2.9	2.7	2.5	2.3	2.4	2.2	2.1	2.0	1.4
			5.0	3.8	3.5	3.3	3.1	3.5	3.3	3.1	2.9	3.0	2.8	2.6	2.5	2.5	2.3	2.2	2.1	1.5
			7.0	3.9	3.7	3.5	3.3	3.6	3.4	3.3	3.1	3.1	3.0	2.8	2.7	2.6	2.5	2.4	2.3	1.7
			10.0	4.0	3.8	3.7	3.6	3.7	3.6	3.5	3.3	3.2	3.1	3.0	2.9	2.7	2.6	2.5	2.5	1.8

