

屋内照明器具特性	
品番 (品名)	L G W 8 5 0 4 0 A F
光源	LDA4L-H-E17/S/4 x1 440.0 lm
管理番号	K0125094(3)DB1
BZ分類	BZ7

器具効率	49%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	25%	床	10%				10%				10%				10%				0%	
下方光束	24%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	2.2	1.6	1.3	1.0	2.0	1.5	1.2	0.9	1.7	1.3	1.0	0.8	1.3	1.0	0.8	0.6	0.4	
	中 0.6	0.8	2.7	2.1	1.7	1.4	2.4	1.9	1.6	1.3	2.0	1.6	1.3	1.1	1.6	1.3	1.1	0.9	0.6	
	否 0.56	1.0	2.9	2.4	2.0	1.7	2.7	2.2	1.9	1.6	2.2	1.8	1.6	1.3	1.8	1.5	1.3	1.1	0.7	
		1.25	3.2	2.7	2.3	2.0	2.9	2.5	2.2	1.9	2.4	2.1	1.8	1.6	2.0	1.7	1.5	1.3	0.9	
下方投影面積	cm ²	1.5	3.4	2.9	2.6	2.3	3.1	2.7	2.4	2.1	2.6	2.3	2.0	1.8	2.1	1.9	1.7	1.5	1.0	
等価発光面積		2.0	3.7	3.3	2.9	2.7	3.4	3.0	2.7	2.5	2.8	2.5	2.3	2.1	2.3	2.1	1.9	1.7	1.2	
取付高さ		器具間隔最大限		2.5	3.8	3.5	3.2	2.9	3.5	3.2	3.0	2.7	3.0	2.7	2.5	2.3	2.4	2.2	2.1	1.3
Hm		横方向 (A)	縦方向 (B)	3.0	4.0	3.7	3.4	3.1	3.7	3.4	3.1	2.9	3.1	2.8	2.7	2.5	2.5	2.3	2.2	1.4
	1.24Hm	1.89Hm	4.0	4.1	3.9	3.6	3.4	3.8	3.6	3.4	3.2	3.2	3.0	2.9	2.7	2.6	2.5	2.4	1.6	
			5.0	4.2	4.0	3.8	3.6	3.9	3.7	3.5	3.4	3.3	3.1	3.0	2.9	2.7	2.6	2.5	1.7	
			7.0	4.4	4.2	4.0	3.9	4.0	3.9	3.7	3.6	3.4	3.3	3.2	3.1	2.8	2.7	2.6	1.8	
			10.0	4.5	4.3	4.2	4.1	4.1	4.0	3.9	3.8	3.5	3.4	3.3	3.2	2.9	2.8	2.8	1.9	

