

屋内照明器具特性

品番 (品名)	L G W 8 5 1 0 3 S														
光源	LDA4L-H-E17/S/4 x1 440.0 lm														
管理番号	K0128279(2)DB1														
BZ分類	BZ5/0.7/BZ4														

器具効率	25%	天井	80%				70%				50%				30%				0%					
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%					
上方光束	0%	反射率	壁	70				70				70				70				0%				
下方光束	25%		床	10%				10%				10%				10%				0%				
室指数			照明率 (X0.01)															ZCM						
保守率	良	0.63	0.6	1.4	1.1	0.9	0.8	1.4	1.1	0.9	0.8	1.3	1.1	0.9	0.8	1.3	1.0	0.9	0.8	1.3	1.0	0.9	0.8	7
	中	0.6	0.8	1.7	1.4	1.2	1.1	1.6	1.4	1.2	1.0	1.6	1.3	1.2	1.0	1.5	1.3	1.1	1.0	1.5	1.3	1.1	1.0	10
	否	0.56	1.0	1.8	1.6	1.4	1.2	1.8	1.5	1.4	1.2	1.7	1.5	1.3	1.2	1.6	1.5	1.3	1.2	1.6	1.5	1.3	1.2	1.2
			1.25	2.0	1.7	1.6	1.4	1.9	1.7	1.5	1.4	1.9	1.7	1.5	1.4	1.8	1.6	1.5	1.4	1.8	1.6	1.5	1.4	1.3
下方投影面積		cm ²	1.5	2.1	1.9	1.7	1.6	2.0	1.8	1.7	1.6	1.9	1.8	1.7	1.8	1.7	1.5	1.4	1.9	1.7	1.6	1.5	1.5	
等価発光面積		cm ²	2.0	2.2	2.0	1.9	1.8	2.2	2.0	1.9	1.8	2.1	2.0	1.8	1.7	2.0	1.9	1.8	1.7	2.0	1.9	1.8	1.7	
取付高さ	器具間隔最大限		2.5	2.3	2.1	2.0	1.9	2.2	2.1	2.0	1.9	2.2	2.1	2.0	1.9	2.1	2.0	1.9	1.8	1.8	1.8	1.8	1.8	
	横方向 (A)	縦方向 (B)	3.0	2.3	2.2	2.1	2.0	2.3	2.2	2.1	2.0	2.2	2.1	2.0	2.0	2.2	2.1	2.0	1.9	1.9	1.9	1.9	1.9	
1.5m	1.85m	1.87m	4.0	2.4	2.3	2.2	2.1	2.4	2.3	2.2	2.1	2.3	2.2	2.1	2.2	2.1	2.2	2.1	2.1	2.1	2.1	2.0	2.0	
2	2.45	2.47	5.0	2.5	2.4	2.3	2.2	2.4	2.3	2.3	2.2	2.4	2.3	2.2	2.2	2.2	2.3	2.2	2.2	2.2	2.2	2.1	2.1	
2.5	3.07	3.09	7.0	2.5	2.4	2.4	2.3	2.5	2.4	2.4	2.3	2.4	2.4	2.3	2.3	2.3	2.4	2.3	2.3	2.3	2.3	2.2	2.2	
3	3.68	3.71	10.0	2.5	2.5	2.5	2.4	2.5	2.5	2.4	2.4	2.5	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.3	2.3	2.2	

