

# 屋内照明器具特性

品番 (品名)	L G W 8 5 1 0 5 S									
光源	LDA4 L - H - E17 / S / 4 × 1					440.0 lm				
管理番号	K0169572 ( 0 ) DB 1									
BZ分類	BZ5 / 0.7 / BZ4									

器具効率	25 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %				
下方光束	25 %		床	10 %				10 %				10 %				10 %				0 %			
室指数	照明率 ( X0.01 )																			ZCM			
保守率	良	0.63	0.6	1.4	1.1	0.9	0.8	1.4	1.1	0.9	0.8	1.3	1.1	0.9	0.8	1.3	1.1	0.9	0.8	1.3	1.1	0.9	0.7
	中	0.6	0.8	1.7	1.4	1.2	1.1	1.7	1.4	1.2	1.1	1.6	1.4	1.2	1.1	1.6	1.4	1.2	1.1	1.5	1.3	1.2	1.0
	否	0.56	1.0	1.9	1.6	1.4	1.3	1.8	1.6	1.4	1.3	1.7	1.5	1.4	1.3	1.7	1.5	1.4	1.3	1.7	1.5	1.4	1.2
			1.25	2.0	1.8	1.6	1.5	2.0	1.8	1.6	1.5	1.9	1.7	1.6	1.4	1.8	1.7	1.5	1.4	1.8	1.7	1.5	1.4
下方投影面積	cm <sup>2</sup>	1.5	2.1	1.9	1.7	1.6	2.1	1.9	1.7	1.6	2.0	1.8	1.7	1.6	1.9	1.8	1.7	1.6	1.9	1.8	1.7	1.6	
等価発光面積		2.0	2.3	2.1	1.9	1.8	2.2	2.0	1.9	1.8	2.1	2.0	1.9	1.8	2.1	1.9	1.8	1.8	2.1	1.9	1.8	1.7	
取付高さ		器具間隔最大限		2.5	2.3	2.2	2.1	2.0	2.3	2.2	2.0	1.9	2.2	2.1	2.0	1.9	2.2	2.1	2.0	1.9	1.8	1.8	1.8
Hm		横方向 (A)	縦方向 (B)	3.0	2.4	2.3	2.2	2.1	2.4	2.2	2.1	2.0	2.3	2.2	2.1	2.0	2.2	2.1	2.1	2.0	1.9	1.9	1.9
Hm	1.25Hm	1.26Hm	4.0	2.5	2.4	2.3	2.2	2.4	2.3	2.3	2.2	2.4	2.3	2.2	2.2	2.3	2.2	2.2	2.1	2.1	2.1	2.1	
			5.0	2.5	2.4	2.4	2.3	2.5	2.4	2.3	2.3	2.4	2.4	2.3	2.2	2.4	2.3	2.2	2.2	2.2	2.2	2.1	
			7.0	2.6	2.5	2.5	2.4	2.5	2.5	2.4	2.4	2.5	2.4	2.4	2.3	2.4	2.4	2.3	2.3	2.3	2.3	2.2	
			10.0	2.6	2.6	2.5	2.5	2.6	2.5	2.5	2.5	2.5	2.5	2.5	2.4	2.4	2.5	2.4	2.4	2.4	2.4	2.3	

