

屋内照明器具特性	
品番(品名)	XAD1108L
光源	LLD2000LCE1 ×1 531.0lm
管理番号	K0187664(2)DR1
BZ分類	BZ2/1.8/BZ3

器具効率	66%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束 66%			床	10%				10%				10%				10%			
室指数		照明率 (X0.01)																Z CM		
保守率	良 0.67	0.6	44	37	33	30	43	37	33	30	42	36	33	30	41	36	32	30	29	
	中 0.63	0.8	50	44	40	37	49	44	40	37	48	43	39	37	46	42	39	37	35	
	否 0.56	1.0	54	49	45	42	53	48	44	42	52	47	44	41	50	46	43	41	40	
	下方投影面積 等価発光面積	cm^2	1.25	57	52	49	46	56	52	49	46	55	51	48	46	53	50	47	45	44
取付高さ	器具間隔最大限		1.5	59	55	52	49	59	55	51	49	57	53	51	48	55	52	50	48	47
	cm^2	cm^2	2.0	62	59	56	53	61	58	55	53	60	57	55	53	58	56	54	52	51
Hm	器具間隔最大限		2.5	64	61	59	56	63	60	58	56	62	59	57	55	60	58	56	55	53
	横方向(A)	縦方向(B)	3.0	65	63	60	58	64	62	60	58	63	61	59	57	61	59	58	57	55
4.0	1.17Hm	1.17Hm	4.0	67	65	63	61	66	64	62	61	64	63	61	60	63	61	60	59	57
5.0			5.0	68	66	64	63	67	65	64	63	65	64	63	62	64	63	62	61	59
7.0			7.0	69	67	66	65	68	67	66	65	66	65	64	64	65	64	63	63	61
10.0			10.0	69	69	68	67	69	68	67	66	67	66	66	65	66	65	65	64	62

