

屋内照明器具特性	
品番 (品名)	LGB10858
光源	LLD2000LCT1 ×1 531.0 lm
管理番号	K0190111 (1) DR 1
BZ分類	BZ3/0.9/BZ2/1.8/BZ3

器具効率	71%	天井	80%				70%				50%				30%				0%				
	上方光束		1%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		70%		床	10%				10%				10%				10%				0%	
		室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	4.6	3.9	3.4	3.1	4.5	3.8	3.4	3.1	4.4	3.8	3.3	3.1	4.2	3.7	3.3	3.0	2.9			
	中	0.63	0.8	5.3	4.6	4.2	3.9	5.2	4.6	4.2	3.9	5.0	4.5	4.1	3.8	4.9	4.4	4.1	3.8	3.7			
	否	0.56	1.0	5.7	5.2	4.7	4.4	5.6	5.1	4.7	4.4	5.5	5.0	4.6	4.4	5.3	4.9	4.6	4.3	4.2			
			1.25	6.1	5.6	5.2	4.9	6.0	5.5	5.2	4.9	5.8	5.4	5.1	4.8	5.7	5.3	5.0	4.8	4.6			
下方投影面積			1.5	6.3	5.9	5.5	5.2	6.2	5.8	5.5	5.2	6.1	5.7	5.4	5.1	5.9	5.6	5.3	5.1	5.0			
			2.0	6.7	6.3	6.0	5.7	6.6	6.2	5.9	5.7	6.4	6.1	5.8	5.6	6.2	5.9	5.7	5.5	5.4			
取付高さ	器具間隔最大限		2.5	6.8	6.5	6.2	6.0	6.7	6.4	6.2	6.0	6.6	6.3	6.1	5.9	6.4	6.2	6.0	5.8	5.7			
	横方向 (A)	縦方向 (B)	3.0	7.0	6.7	6.5	6.2	6.9	6.6	6.4	6.2	6.7	6.5	6.3	6.1	6.5	6.3	6.2	6.0	5.9			
Hm	1.33Hm	1.33Hm	4.0	7.1	6.9	6.7	6.5	7.0	6.8	6.7	6.5	6.9	6.7	6.5	6.4	6.7	6.5	6.4	6.3	6.1			
			5.0	7.2	7.1	6.9	6.7	7.1	7.0	6.8	6.7	7.0	6.8	6.7	6.6	6.8	6.7	6.6	6.5	6.3			
			7.0	7.3	7.2	7.1	7.0	7.3	7.1	7.0	6.9	7.1	7.0	6.9	6.8	6.9	6.8	6.7	6.7	6.5			
			10.0	7.4	7.3	7.2	7.2	7.3	7.3	7.2	7.1	7.2	7.1	7.0	7.0	7.0	6.9	6.9	6.8	6.6			

