

屋内照明器具特性

品番 (品名)	LGB81649															
光源	LDA4 WW- H- E17 / S / 4 ×1 440.0 1 m															
管理番号	K0187732 (0) DB 1															
BZ分類	BZ5 / 1.1 / BZ4															

器具効率	61 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																ZCM		
下方光束	61 %																				
保守率	良 中 否 0.67 0.63 0.56	0.6	3.4	2.7	2.2	1.8	3.3	2.6	2.2	1.8	3.2	2.6	2.1	1.8	3.1	2.5	2.1	1.8	1.7		
		0.8	4.1	3.4	2.9	2.5	4.0	3.3	2.9	2.5	3.8	3.2	2.8	2.5	3.7	3.2	2.8	2.5	2.4		
		1.0	4.5	3.9	3.4	3.0	4.4	3.8	3.4	3.0	4.2	3.7	3.3	3.0	4.1	3.6	3.3	3.0	2.9		
		1.25	4.9	4.3	3.9	3.6	4.8	4.3	3.9	3.5	4.6	4.2	3.8	3.5	4.5	4.1	3.7	3.5	3.3		
下方投影面積	c m ²	1.5	5.2	4.7	4.3	3.9	5.1	4.6	4.2	3.9	4.9	4.5	4.2	3.9	4.7	4.4	4.1	3.8	3.7		
		2.0	5.5	5.1	4.8	4.5	5.5	5.1	4.7	4.5	5.3	4.9	4.7	4.4	5.1	4.8	4.6	4.4	4.2		
取付高さ	器具間隔最大限		2.5	5.8	5.4	5.1	4.9	5.7	5.3	5.1	4.8	5.5	5.2	5.0	4.8	5.3	5.1	4.9	4.6		
	横方向 (A)	縦方向 (B)	3.0	5.9	5.6	5.3	5.1	5.8	5.5	5.3	5.1	5.6	5.4	5.2	5.0	5.5	5.3	5.1	4.9	4.8	
H m	1.36 H m	1.36 H m	4.0	6.1	5.9	5.6	5.5	6.0	5.8	5.6	5.4	5.8	5.7	5.5	5.3	5.7	5.5	5.4	5.3	5.1	
			5.0	6.2	6.0	5.8	5.7	6.1	5.9	5.8	5.6	6.0	5.8	5.7	5.5	5.8	5.7	5.6	5.5	5.3	
			7.0	6.3	6.2	6.1	5.9	6.2	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.9	5.9	5.8	5.7	5.5	
			10.0	6.4	6.3	6.2	6.1	6.3	6.2	6.2	6.1	6.2	6.1	6.0	6.0	6.0	6.0	5.9	5.9	5.7	

