

屋内照明器具特性

品番 (品名)	LGB87001F															
光源	LDA4L-H-E17/S/4 ×1 440.0lm															
管理番号	K0122398(1)DB1															
BZ分類	BZ4/0.7/BZ3/0.9/BZ4															

器具効率	34%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	4%	室指数	照明率 (X0.01) ZCM																		
下方光束	30%																				
保守率	良 0.63 中 0.6 否 0.56	0.6	20	16	14	12	19	16	14	12	18	15	13	12	17	14	13	11	11		
		0.8	23	20	17	15	22	19	17	15	21	18	16	15	20	17	16	14	13		
		1.0	25	22	20	18	24	21	19	18	23	20	19	17	22	19	18	17	15		
		1.25	27	24	22	20	26	23	21	20	25	22	21	19	23	21	20	19	17		
下方投影面積	cm ²	1.5	28	26	24	22	27	25	23	22	26	24	22	21	24	23	21	20	19		
		2.0	30	28	26	24	29	27	25	24	27	26	24	23	26	25	23	22	21		
等価発光面積	cm ²	2.5	31	29	28	26	30	28	27	26	28	27	26	25	27	26	25	24	22		
		3.0	32	30	29	27	31	29	28	27	29	28	27	26	28	27	26	25	23		
取付高さ	器具間隔最大限		4.0	33	31	30	29	32	31	30	29	30	29	28	28	29	28	27	26	25	
	横方向 (A)	縦方向 (B)	5.0	33	32	31	30	32	31	31	30	31	30	29	29	29	28	28	27	25	
Hm	0.74Hm	1.24Hm	7.0	34	33	32	32	33	32	32	31	31	31	30	30	30	29	29	28	26	
			10.0	34	34	33	33	33	33	32	32	32	31	31	31	30	30	30	29	27	

