

# 屋内照明器具特性

品番 (品名)	XND9996SVZ	
光源	LED3500_80_16080 x1 16080.0 1m	
管理番号	K0188262(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%				
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%			
下方光束	100%		床	10%				10%				10%				10%				0%			
		室指数	照明率 ( X0.01 )																ZCM				
保守率	良	0.76	0.6	74	65	60	56	73	65	60	56	71	64	59	56	69	63	59	56	54			
	中	0.72	0.8	82	75	70	66	81	74	69	66	79	73	69	66	78	72	68	65	64			
	否	0.64	1.0	88	81	76	73	87	80	76	72	84	79	75	72	83	78	74	72	70			
下方投影面積	cm <sup>2</sup>	等価発光面積	cm <sup>2</sup>	1.25	92	86	82	78	91	85	81	78	89	84	80	78	87	83	80	77	75		
				1.5	95	90	86	83	94	89	85	82	91	87	84	82	89	86	83	81	79		
取付高さ	器具間隔最大限		Hm	0.72Hm	0.72Hm	2.5	101	97	94	92	99	96	94	91	97	94	92	90	95	93	91	89	87
	横方向 (A)	縦方向 (B)				3.0	102	99	96	94	101	98	96	94	99	96	94	92	96	95	93	91	89
Hm	0.72Hm	0.72Hm	4.0	104	101	99	97	102	100	98	97	100	98	97	95	98	97	95	94	92			
			5.0	105	103	101	100	104	102	100	99	101	100	98	97	99	98	97	96	93			
			7.0	106	104	103	102	105	103	102	101	102	101	100	99	100	99	99	98	95			
			10.0	107	106	105	104	106	105	104	103	103	102	102	101	101	100	100	99	97			

