

屋内照明器具特性	
品番 (品名)	XLJ 4301
光源	LED5000_88_6900 x1 6900.0 lm
管理番号	K0189570(0)DR1
BZ分類	BZ4

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 ( X0.01)																ZCM	
保守率	良中否	0.6	59	47	39	34	57	46	39	34	55	45	39	34	53	44	38	34	32	
		0.8	69	58	51	45	68	58	50	45	65	56	50	45	63	55	49	45	43	
		1.0	76	66	59	53	75	65	58	53	72	64	58	53	69	62	57	53	50	
		1.25	82	73	67	61	81	72	66	61	78	71	65	61	75	69	64	60	58	
下方投影面積	c m <sup>2</sup>	1.5	86	78	72	67	85	77	72	67	82	75	70	66	79	74	69	66	63	
		2.0	92	85	80	76	90	84	79	75	87	82	78	74	85	80	77	73	71	
取付高さ	器具間隔最大限		2.5	95	90	85	81	94	89	84	81	91	86	83	80	88	85	81	79	76
	横方向 (A)	縦方向 (B)	3.0	97	93	89	85	96	92	88	84	93	89	86	83	90	87	85	82	80
1.5m	1.94m	1.93m	4.0	100	97	93	90	99	95	92	90	96	93	91	88	94	91	89	87	84
2	2.58	2.53	5.0	102	99	96	94	100	98	95	93	98	95	93	91	95	93	92	90	87
2.5	3.22	3.16	7.0	104	102	100	98	102	100	98	97	100	98	97	95	97	96	95	93	91
3	3.86	3.79	10.0	105	104	102	101	104	102	101	100	101	100	99	98	99	98	97	96	93

