

屋内照明器具特性

品番 (品名)	LSEB4106Z															
光源	LDA4L-H-E17/S/4 x1 440.0lm															
管理番号	K0187162(0)DR1															
BZ分類	BZ6															

器具効率	95%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	36%	反射率	10%				10%				10%				10%				0%	
下方光束	59%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01) ZCM																	
保守率	良 中 否	0.67	0.6	47	36	29	24	44	34	27	22	38	30	24	20	33	26	22	18	14
		0.63	0.8	55	44	37	31	52	42	35	30	45	37	31	27	39	32	28	24	19
			1.0	61	50	43	37	57	48	41	36	49	42	36	32	43	37	32	29	23
		0.56	1.25	66	56	49	43	62	53	47	41	54	47	42	37	46	41	37	33	26
下方投影面積	c m ²	1.5	70	61	54	48	65	57	51	46	57	50	45	41	49	44	40	37	29	
		2.0	75	67	61	55	70	63	57	53	61	56	51	47	53	49	45	42	33	
取付高さ	器具間隔最大限		2.5	78	71	66	61	73	67	62	58	64	59	55	52	56	52	49	46	36
	横方向 (A)	縦方向 (B)	3.0	80	74	69	65	76	70	65	61	66	62	58	55	57	54	51	49	39
H m	1.23H m	1.27H m	4.0	83	78	74	70	78	74	70	66	69	66	62	59	60	57	55	53	42
			5.0	85	81	77	74	80	77	73	70	71	68	65	63	62	59	57	55	44
			7.0	88	84	81	79	83	80	77	74	73	71	69	66	64	62	60	59	47
			10.0	90	87	85	82	85	82	80	78	75	73	71	70	66	64	63	62	50

