

屋内照明器具特性	
品番 (品名)	L G W 8 5 2 1 9 F
光源	LDA4L-H-E17/S/4 x1 440.0 lm
管理番号	K0189673(0)DB1
BZ分類	BZ7

器具効率	48%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	8%	床	10%				10%				10%				10%				0%	
下方光束	40%		室指数	照明率 ( X 0.01 )																ZCM
保守率	良 0.63	0.6	2.3	1.7	1.3	1.0	2.2	1.6	1.2	1.0	2.0	1.5	1.2	9	1.8	1.4	1.1	9	7	
	中 0.6	0.8	2.8	2.1	1.7	1.4	2.6	2.0	1.6	1.3	2.4	1.9	1.5	1.3	2.1	1.7	1.4	1.2	1.0	
	否 0.56	1.0	3.1	2.4	2.0	1.7	2.9	2.4	1.9	1.6	2.6	2.2	1.8	1.5	2.4	2.0	1.7	1.5	1.2	
下方投影面積	cm <sup>2</sup>	1.25	3.3	2.8	2.3	2.0	3.2	2.7	2.3	1.9	2.9	2.4	2.1	1.8	2.6	2.3	2.0	1.7	1.5	
		1.5	3.5	3.0	2.6	2.3	3.4	2.9	2.5	2.2	3.1	2.7	2.3	2.1	2.8	2.5	2.2	1.9	1.7	
等価発光面積	cm <sup>2</sup>	2.0	3.8	3.4	3.0	2.7	3.7	3.2	2.9	2.6	3.3	3.0	2.7	2.4	3.0	2.7	2.5	2.3	2.0	
		2.5	4.0	3.6	3.2	2.9	3.8	3.5	3.1	2.9	3.5	3.2	2.9	2.7	3.2	3.0	2.7	2.5	2.2	
取付高さ	器具間隔最大限		3.0	4.1	3.8	3.5	3.2	4.0	3.6	3.3	3.1	3.6	3.4	3.1	2.9	3.3	3.1	2.9	2.7	2.4
	横方向 (A)	縦方向 (B)	4.0	4.3	4.0	3.7	3.5	4.2	3.9	3.6	3.4	3.8	3.6	3.4	3.2	3.5	3.3	3.2	3.0	2.7
Hm	1.46Hm	1.45Hm	5.0	4.4	4.2	3.9	3.7	4.3	4.0	3.8	3.6	3.9	3.7	3.6	3.4	3.6	3.5	3.3	3.2	2.8
			7.0	4.6	4.4	4.2	4.0	4.4	4.2	4.0	3.9	4.1	3.9	3.8	3.6	3.8	3.7	3.5	3.4	3.1
			10.0	4.7	4.5	4.4	4.2	4.5	4.4	4.2	4.1	4.2	4.1	4.0	3.9	3.9	3.8	3.7	3.6	3.3

