

屋内照明器具特性

品番 (品名)	LGB15026F																
光源	LDA8L-D-G-E17/S/Z6 ×1 760.0 1 m																
管理番号	K0169960(0)DR1																
BZ分類	BZ7																

器具効率	80%	天井	80%				70%				50%				30%				0%		
	上方光束		32%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		48%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.67	0.6	3.8	2.8	2.1	1.7	3.5	2.6	2.0	1.6	3.0	2.3	1.8	1.4	2.5	2.0	1.5	1.2	0.9	
	中	0.63	0.8	4.4	3.4	2.8	2.3	4.1	3.2	2.6	2.2	3.5	2.8	2.3	1.9	3.0	2.4	2.0	1.7	1.2	
	否	0.56	1.0	4.9	3.9	3.3	2.7	4.5	3.7	3.1	2.6	3.9	3.2	2.7	2.3	3.3	2.7	2.3	2.0	1.5	
			1.25	5.3	4.4	3.7	3.2	4.9	4.1	3.5	3.1	4.2	3.6	3.1	2.7	3.6	3.1	2.7	2.4	1.7	
下方投影面積			1.5	5.6	4.8	4.1	3.6	5.2	4.5	3.9	3.4	4.5	3.9	3.4	3.0	3.8	3.3	3.0	2.6	2.0	
			2.0	6.0	5.3	4.7	4.2	5.6	5.0	4.5	4.0	4.9	4.3	3.9	3.5	4.1	3.7	3.4	3.1	2.3	
取付高さ	器具間隔最大限		2.5	6.3	5.7	5.2	4.7	5.9	5.3	4.8	4.4	5.1	4.7	4.3	3.9	4.4	4.0	3.7	3.4	2.6	
	横方向 (A)	縦方向 (B)	3.0	6.5	6.0	5.5	5.0	6.1	5.6	5.2	4.8	5.3	4.9	4.5	4.2	4.5	4.2	3.9	3.7	2.8	
H _m	1.03H _m	1.03H _m	4.0	6.8	6.3	5.9	5.5	6.4	6.0	5.6	5.2	5.6	5.2	4.9	4.6	4.8	4.5	4.3	4.0	3.1	
			5.0	7.0	6.6	6.2	5.9	6.6	6.2	5.9	5.5	5.7	5.4	5.2	4.9	5.0	4.7	4.5	4.3	3.3	
			7.0	7.2	6.9	6.6	6.3	6.8	6.5	6.2	6.0	5.9	5.7	5.5	5.3	5.2	5.0	4.8	4.6	3.6	
			10.0	7.4	7.1	6.9	6.7	7.0	6.7	6.5	6.3	6.1	5.9	5.8	5.6	5.3	5.2	5.1	4.9	3.9	

