

屋内照明器具特性	
品番 (品名)	L G W C 5 6 0 2 0 B U
光源	LDA4L-H-E17/S/4 ×1 440.0 1 m
管理番号	K0125232(1)DB1
BZ分類	BZ5

器具効率	42 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	6 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	36 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63 中 0.6 否 0.56	0.6	22	17	14	12	21	17	14	11	20	16	13	11	18	15	12	11	9	
		0.8	26	21	18	16	25	21	18	15	23	20	17	15	22	18	16	14	13	
		1.0	29	24	21	19	28	24	21	18	26	22	20	17	24	21	19	17	15	
		1.25	31	27	24	22	30	26	23	21	28	25	22	20	26	23	21	19	18	
下方投影面積	c m ²	1.5	33	29	26	24	32	28	26	23	30	27	24	22	27	25	23	21	19	
		2.0	36	32	30	27	34	31	29	27	32	29	27	25	30	28	26	24	22	
取付高さ	器具間隔最大限		2.5	37	34	32	30	36	33	31	29	33	31	29	28	31	29	28	26	24
	横方向 (A)	縦方向 (B)	3.0	38	36	33	31	37	34	32	31	34	32	31	29	32	30	29	28	25
H m	1.27 H m	1.27 H m	4.0	39	37	36	34	38	36	35	33	36	34	33	32	33	32	31	30	27
			5.0	40	39	37	36	39	37	36	35	37	35	34	33	34	33	32	31	29
			7.0	41	40	39	38	40	39	38	37	38	37	36	35	35	34	34	33	30
			10.0	42	41	40	39	41	40	39	38	38	38	37	36	36	36	35	34	31

