

# 屋内照明器具特性

|         |                |           |
|---------|----------------|-----------|
| 品番 (品名) | FYY26661C      |           |
| 光源      | FYY26661Z x1   | 2390.0 lm |
| 管理番号    | K0125494(5)DB1 |           |
| BZ分類    | BZ3            |           |

|        |                  |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |    |     |
|--------|------------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|-----|
| 器具効率   | 100%             | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |    | 0% |    |     |
|        | 上方光束<br>0%       |         | 反射率  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10 | 0% |     |
| 下方光束   | 100%             | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |    |    | 0% |     |
| 室指数    | 照明率 ( X0.01 )    |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |    | ZCM |
| 保守率    | 良<br>中<br>否      | 0.77    | 0.6  | 64  | 53  | 46  | 42  | 63  | 53  | 46  | 41  | 60  | 52  | 46  | 41  | 59  | 51 | 45 | 41 | 39 |     |
|        |                  | 0.72    | 0.8  | 74  | 64  | 57  | 53  | 72  | 63  | 57  | 53  | 70  | 62  | 57  | 52  | 68  | 61 | 56 | 52 | 50 |     |
|        |                  | 0.68    | 1.0  | 80  | 71  | 65  | 60  | 79  | 71  | 65  | 60  | 76  | 69  | 64  | 60  | 74  | 68 | 63 | 59 | 57 |     |
|        |                  |         | 1.25 | 85  | 78  | 72  | 67  | 84  | 77  | 71  | 67  | 81  | 75  | 70  | 67  | 79  | 74 | 70 | 66 | 64 |     |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 89   | 82  | 77  | 72  | 88  | 81  | 76  | 72  | 85  | 79  | 75  | 71  | 83  | 78  | 74 | 71 | 69 |    |     |
|        |                  | 2.0     | 94   | 88  | 83  | 79  | 92  | 87  | 83  | 79  | 90  | 85  | 81  | 78  | 87  | 83  | 80 | 77 | 75 |    |     |
| 取付高さ   | 器具間隔最大限          |         | 2.5  | 97  | 92  | 88  | 84  | 95  | 91  | 87  | 84  | 93  | 89  | 85  | 83  | 90  | 87 | 84 | 82 | 79 |     |
|        | 横方向 (A)          | 縦方向 (B) | 3.0  | 98  | 94  | 91  | 88  | 97  | 93  | 90  | 87  | 95  | 91  | 88  | 86  | 92  | 89 | 87 | 85 | 82 |     |
| 1.5m   | 1.92m            | 1.87m   | 4.0  | 101 | 98  | 95  | 92  | 100 | 97  | 94  | 91  | 97  | 94  | 92  | 90  | 95  | 93 | 91 | 89 | 86 |     |
| 2      | 2.55             | 2.35    | 5.0  | 102 | 100 | 97  | 95  | 101 | 99  | 96  | 94  | 99  | 96  | 95  | 93  | 96  | 94 | 93 | 91 | 89 |     |
| 2.5    | 3.17             | 2.84    | 7.0  | 104 | 102 | 100 | 98  | 103 | 101 | 99  | 98  | 100 | 99  | 97  | 96  | 98  | 97 | 96 | 94 | 92 |     |
| 3      | 3.79             | 3.35    | 10.0 | 105 | 104 | 103 | 101 | 104 | 103 | 102 | 100 | 102 | 101 | 100 | 99  | 99  | 98 | 98 | 97 | 94 |     |

