

# 屋内照明器具特性

品番 (品名)	XLGE532BHF																
光源	LDA4L-H-E17/S/4 x1 440.0lm																
管理番号	K0158843(0)DB1																
BZ分類	BZ10																

器具効率	28%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	15%	壁	10%				10%				10%				10%				0%	
下方光束	13%	床	10%				10%				10%				10%				0%	
		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.63	0.6	11	8	5	4	10	7	5	3	8	5	4	2	6	4	3	2	0
	中	0.6	0.8	13	10	7	5	12	9	7	5	10	7	5	4	7	5	4	3	1
	否	0.56	1.0	15	11	9	7	13	10	8	6	11	8	6	5	8	6	5	4	1
			1.25	16	13	11	9	15	12	10	8	12	9	8	6	9	7	6	5	2
下方投影面積		cm <sup>2</sup>	1.5	18	14	12	10	16	13	11	9	13	11	9	7	10	8	7	6	3
等価発光面積		cm <sup>2</sup>	2.0	19	16	14	12	17	15	13	11	14	12	10	9	11	9	8	7	4
取付高さ	器具間隔最大限		2.5	20	18	16	14	18	16	14	13	15	13	12	10	12	10	9	8	5
	横方向 (A)	縦方向 (B)	3.0	21	19	17	15	19	17	15	14	16	14	13	11	12	11	10	9	5
Hm	0.00Hm	0.00Hm	4.0	22	20	18	17	20	19	17	16	17	15	14	13	13	12	11	10	6
			5.0	23	21	20	18	21	19	18	17	17	16	15	14	14	13	12	11	7
			7.0	24	22	21	20	22	21	19	18	18	17	16	15	15	14	13	13	8
			10.0	24	23	22	21	22	22	21	20	19	18	17	17	15	15	14	14	9

