

| | |
|----------|-------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | FYY44045 (JYOUJI) |
| 光源 | LDL40S.N/29/38-K ×1 3800.0 lm |
| 管理番号 | K0171212 (1) DB1 |
| BZ分類 | BZ7 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|----------------------------|---------|-------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 26% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 74% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 0.81 中 0.77 否 0.68 | 0.6 | 48 | 35 | 26 | 20 | 45 | 33 | 25 | 20 | 40 | 30 | 23 | 18 | 35 | 27 | 21 | 17 | 13 | |
| | | 0.8 | 56 | 44 | 35 | 29 | 53 | 42 | 33 | 27 | 47 | 38 | 31 | 25 | 42 | 34 | 28 | 23 | 19 | |
| | | 1.0 | 63 | 50 | 41 | 35 | 59 | 48 | 40 | 33 | 52 | 43 | 36 | 31 | 46 | 39 | 33 | 28 | 23 | |
| | | 1.25 | 68 | 57 | 48 | 41 | 65 | 54 | 46 | 40 | 57 | 49 | 42 | 37 | 51 | 44 | 38 | 34 | 28 | |
| 下方投影面積 | c m ² | 1.5 | 72 | 62 | 53 | 47 | 69 | 59 | 51 | 45 | 61 | 53 | 47 | 41 | 54 | 48 | 43 | 38 | 32 | |
| | | 2.0 | 78 | 69 | 61 | 55 | 74 | 66 | 59 | 53 | 67 | 60 | 54 | 49 | 59 | 54 | 49 | 45 | 37 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 82 | 74 | 67 | 61 | 78 | 70 | 64 | 59 | 70 | 64 | 59 | 54 | 63 | 58 | 53 | 50 | 42 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 85 | 77 | 71 | 65 | 81 | 74 | 68 | 63 | 73 | 67 | 62 | 58 | 65 | 61 | 57 | 53 | 45 |
| 1.5m | 2.74m | 2.17m | 4.0 | 89 | 82 | 77 | 72 | 84 | 79 | 74 | 69 | 76 | 72 | 68 | 64 | 69 | 65 | 62 | 59 | 50 |
| 2 | 3.6 | 2.74 | 5.0 | 91 | 86 | 81 | 76 | 87 | 82 | 77 | 73 | 79 | 75 | 71 | 68 | 71 | 68 | 65 | 62 | 53 |
| 2.5 | 4.46 | 3.33 | 7.0 | 94 | 90 | 86 | 82 | 90 | 86 | 82 | 79 | 82 | 78 | 76 | 73 | 74 | 71 | 69 | 67 | 58 |
| 3 | 5.32 | 3.94 | 10.0 | 96 | 93 | 90 | 87 | 92 | 89 | 86 | 84 | 84 | 82 | 79 | 77 | 76 | 74 | 73 | 71 | 61 |

