

# 屋内照明器具特性

|         |                     |            |
|---------|---------------------|------------|
| 品番 (品名) | XND9996SNZ          |            |
| 光源      | LED5000_80_16105 x1 | 16105.0 1m |
| 管理番号    | K0188262(0)DB1      |            |
| BZ分類    | BZ1                 |            |

| 器具効率   | 100%    | 天井              | 80%          |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|--------|---------|-----------------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
|        |         |                 | 70           | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  |     |    |
| 上方光束   | 0%      | 反射率             | 壁            | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
| 下方光束   | 100%    |                 | 床            | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
|        |         | 室指数             | 照明率 ( X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率    | 良       | 0.76            | 0.6          | 74  | 65  | 60  | 56  | 73  | 65  | 60  | 56  | 71  | 64  | 59  | 56  | 69  | 63  | 59  | 56  | 54 |
|        | 中       | 0.72            | 0.8          | 82  | 75  | 70  | 66  | 81  | 74  | 69  | 66  | 79  | 73  | 69  | 66  | 78  | 72  | 68  | 65  | 64 |
|        | 否       | 0.64            | 1.0          | 88  | 81  | 76  | 73  | 87  | 80  | 76  | 72  | 84  | 79  | 75  | 72  | 83  | 78  | 74  | 72  | 70 |
| 下方投影面積 | 等価発光面積  | cm <sup>2</sup> | 1.25         | 92  | 86  | 82  | 78  | 91  | 85  | 81  | 78  | 89  | 84  | 80  | 78  | 87  | 83  | 80  | 77  | 75 |
|        |         |                 | 1.5          | 95  | 90  | 86  | 83  | 94  | 89  | 85  | 82  | 91  | 87  | 84  | 82  | 89  | 86  | 83  | 81  | 79 |
| 取付高さ   | 器具間隔最大限 |                 | 2.0          | 98  | 94  | 91  | 88  | 97  | 93  | 90  | 88  | 95  | 92  | 89  | 87  | 93  | 90  | 88  | 86  | 84 |
|        | 横方向 (A) | 縦方向 (B)         | 2.5          | 101 | 97  | 94  | 92  | 99  | 96  | 94  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91  | 89  | 87 |
| Hm     | 0.72Hm  | 0.72Hm          | 3.0          | 102 | 99  | 96  | 94  | 101 | 98  | 96  | 94  | 99  | 96  | 94  | 92  | 96  | 95  | 93  | 91  | 89 |
|        |         |                 | 4.0          | 104 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 97  | 95  | 98  | 97  | 95  | 94  | 92 |
|        |         |                 | 5.0          | 105 | 103 | 101 | 100 | 104 | 102 | 100 | 99  | 101 | 100 | 98  | 97  | 99  | 98  | 97  | 96  | 93 |
|        |         |                 | 7.0          | 106 | 104 | 103 | 102 | 105 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 99  | 98  | 95 |
|        |         |                 | 10.0         | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 99  | 97 |

