

屋内照明器具特性	
品番 (品名)	FYY46000
光源	LDL40S.N/29/38K(3800) ×1 3800.0 1m
管理番号	K0124842(0)DB1
BZ分類	BZ10/0.7/BZ9

器具効率	58%	天井	80%				70%				50%				30%				0%
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	54%	床	10%				10%				10%				10%				0%
下方光束	4%	室指数	照明率 (X0.01)																ZCM
保守率	良 0.81	0.6	25	19	15	12	21	16	13	11	15	11	9	7	9	7	6	5	0
	中 0.77	0.8	29	23	19	16	25	20	17	14	18	14	12	10	11	9	7	6	0
	否 0.68	1.0	33	27	23	20	28	23	20	18	20	17	14	13	12	10	9	8	0
			1.25	36	31	27	24	31	26	23	21	21	19	17	15	13	11	10	9
下方投影面積		1.5	38	33	29	27	33	29	26	23	23	20	18	17	14	12	11	10	1
等価発光面積		2.0	41	37	34	31	35	32	29	27	25	23	21	19	15	14	13	12	1
取付高さ	器具間隔最大限		2.5	43	39	36	34	37	34	32	30	26	24	23	21	16	15	14	1
	横方向 (A)	縦方向 (B)	3.0	44	41	38	36	38	36	33	31	27	25	24	23	16	16	15	2
1.5m	0	2	4.0	45	43	41	39	39	37	36	34	28	27	26	25	17	17	16	2
2	0	2.57	5.0	46	44	43	41	40	39	37	36	29	28	27	26	18	17	17	2
2.5	0	3.12	7.0	48	46	45	43	42	40	39	38	30	29	28	27	18	18	18	2
3	0	3.68	10.0	49	48	46	45	42	41	41	40	30	30	29	29	19	19	18	2

