

屋内照明器具特性	
品番 (品名)	L G W 8 5 0 7 6 S
光源	LDA4L-H-E17/S/4 x1 440.0 lm
管理番号	K0125801(1)DB1
BZ分類	BZ10/0.7/BZ9

器具効率	32%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	14%	床	10%				10%				10%				10%				0%	
下方光束	18%		10%				10%				10%				10%				0%	
室指数		照明率 (X 0.01)																ZCM		
保守率	良	0.63	0.6	1.4	9	7	5	12	9	6	5	10	7	5	4	8	6	4	3	2
	中	0.6	0.8	1.6	12	9	7	15	11	9	7	12	9	7	6	10	8	6	5	3
	否	0.56	1.0	1.8	14	11	9	17	13	10	8	14	11	9	7	11	9	7	6	4
			1.25	2.0	1.6	1.3	1.1	1.8	1.5	1.2	1.0	1.5	1.3	1.0	9	1.2	1.0	9	7	5
下方投影面積		cm ²	1.5	2.1	1.8	1.5	1.3	1.9	1.6	1.4	1.2	1.6	1.4	1.2	1.0	1.3	1.1	1.0	8	6
等価発光面積		cm ²	2.0	2.3	2.0	1.7	1.5	2.1	1.8	1.6	1.4	1.8	1.6	1.4	1.2	1.5	1.3	1.2	1.0	7
取付高さ	器具間隔最大限		2.5	2.4	2.1	1.9	1.7	2.2	2.0	1.8	1.6	1.9	1.7	1.5	1.4	1.6	1.4	1.3	1.2	8
	横方向 (A)	縦方向 (B)	3.0	2.5	2.3	2.0	1.9	2.3	2.1	1.9	1.7	2.0	1.8	1.6	1.5	1.7	1.5	1.4	1.3	9
Hm	0.00Hm	1.44Hm	4.0	2.6	2.4	2.2	2.1	2.4	2.3	2.1	1.9	2.1	1.9	1.8	1.7	1.8	1.6	1.5	1.4	10
			5.0	2.7	2.5	2.4	2.2	2.5	2.4	2.2	2.1	2.2	2.0	1.9	1.8	1.8	1.7	1.6	1.5	11
			7.0	2.8	2.7	2.5	2.4	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.0	1.9	1.8	1.8	1.7	1.3
			10.0	2.9	2.8	2.7	2.6	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.0	1.9	1.9	1.8	1.4

