

|          |                             |
|----------|-----------------------------|
| 屋内照明器具特性 |                             |
| 品番 (品名)  | L G W 8 5 1 0 3 S           |
| 光源       | LDA4L-H-E17/S/4 x1 440.0 lm |
| 管理番号     | K0128279(2)DB1              |
| BZ分類     | BZ5/0.7/BZ4                 |

|        |                 |               |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|-----------------|---------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 25%             | 天井            | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |     |     |     |
|        |                 |               | 壁    | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |     |     |     |
| 上方光束   | 0%              | 床             | 10%  |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |     |     |     |
| 下方光束   | 25%             |               | 10%  |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |     |     |     |
| 室指数    |                 | 照明率 ( X0.01 ) |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |     |     |     |     |     |
| 保守率    | 良               | 0.63          | 0.6  | 1.4 | 1.1 | 0.9 | 0.8 | 1.4 | 1.1 | 0.9 | 0.8 | 1.3 | 1.1 | 0.9 | 0.8 | 1.3 | 1.0 | 0.9 | 0.8 | 1.0 | 0.9 | 0.8 | 0.7 |
|        | 中               | 0.6           | 0.8  | 1.7 | 1.4 | 1.2 | 1.1 | 1.6 | 1.4 | 1.2 | 1.0 | 1.6 | 1.3 | 1.2 | 1.0 | 1.5 | 1.3 | 1.1 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
|        | 否               | 0.56          | 1.0  | 1.8 | 1.6 | 1.4 | 1.2 | 1.8 | 1.5 | 1.4 | 1.2 | 1.7 | 1.5 | 1.3 | 1.2 | 1.6 | 1.5 | 1.3 | 1.2 | 1.2 | 1.2 | 1.2 | 1.2 |
|        |                 |               | 1.25 | 2.0 | 1.7 | 1.6 | 1.4 | 1.9 | 1.7 | 1.5 | 1.4 | 1.9 | 1.7 | 1.5 | 1.4 | 1.8 | 1.6 | 1.5 | 1.4 | 1.3 | 1.3 | 1.3 | 1.3 |
| 下方投影面積 | cm <sup>2</sup> | 1.5           | 2.1  | 1.9 | 1.7 | 1.6 | 2.0 | 1.8 | 1.7 | 1.6 | 1.9 | 1.8 | 1.7 | 1.5 | 1.9 | 1.7 | 1.6 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 |     |
| 等価発光面積 | cm <sup>2</sup> | 2.0           | 2.2  | 2.0 | 1.9 | 1.8 | 2.2 | 2.0 | 1.9 | 1.8 | 2.1 | 2.0 | 1.8 | 1.7 | 2.0 | 1.8 | 1.7 | 1.6 | 1.7 | 1.7 | 1.7 | 1.7 |     |
| 取付高さ   | 器具間隔最大限         |               | 2.5  | 2.3 | 2.1 | 2.0 | 1.9 | 2.2 | 2.1 | 2.0 | 1.9 | 2.2 | 2.1 | 2.0 | 1.9 | 2.1 | 2.0 | 1.9 | 1.8 | 1.8 | 1.8 | 1.8 | 1.8 |
|        | 横方向 (A)         | 縦方向 (B)       | 3.0  | 2.3 | 2.2 | 2.1 | 2.0 | 2.3 | 2.2 | 2.1 | 2.0 | 2.2 | 2.1 | 2.0 | 2.0 | 2.2 | 2.1 | 2.0 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 |
| 1.5m   | 1.85 m          | 1.87 m        | 4.0  | 2.4 | 2.3 | 2.2 | 2.1 | 2.4 | 2.3 | 2.2 | 2.1 | 2.3 | 2.2 | 2.2 | 2.1 | 2.2 | 2.2 | 2.2 | 2.1 | 2.1 | 2.1 | 2.1 | 2.0 |
| 2      | 2.45            | 2.47          | 5.0  | 2.5 | 2.4 | 2.3 | 2.2 | 2.4 | 2.3 | 2.3 | 2.2 | 2.4 | 2.3 | 2.2 | 2.2 | 2.3 | 2.2 | 2.2 | 2.2 | 2.2 | 2.1 | 2.1 | 2.1 |
| 2.5    | 3.07            | 3.09          | 7.0  | 2.5 | 2.4 | 2.4 | 2.3 | 2.5 | 2.4 | 2.4 | 2.3 | 2.4 | 2.4 | 2.3 | 2.3 | 2.4 | 2.3 | 2.3 | 2.3 | 2.2 | 2.2 | 2.2 | 2.2 |
| 3      | 3.68            | 3.71          | 10.0 | 2.5 | 2.5 | 2.5 | 2.4 | 2.5 | 2.5 | 2.4 | 2.4 | 2.5 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.3 | 2.3 | 2.3 | 2.2 | 2.2 |

