

屋内照明器具特性	
品番 (品名)	L G W 8 5 1 0 2 B F
光源	LDA4 L - H - E17 / S / 4 × 1 440.0 l m
管理番号	K0169572 (0) DB 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率	25 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	25 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01)																Z C M	
保守率	良	0.63	0.6	1.4	1.1	0.9	0.8	1.4	1.1	0.9	0.8	1.3	1.1	0.9	0.8	1.3	1.1	0.9	0.8	0.7
	中	0.6	0.8	1.7	1.4	1.2	1.1	1.7	1.4	1.2	1.1	1.6	1.4	1.2	1.1	1.5	1.3	1.2	1.1	1.0
	否	0.56	1.0	1.9	1.6	1.4	1.3	1.8	1.6	1.4	1.3	1.7	1.5	1.4	1.3	1.7	1.5	1.4	1.2	1.2
			1.25	2.0	1.8	1.6	1.5	2.0	1.8	1.6	1.5	1.9	1.7	1.6	1.4	1.8	1.7	1.5	1.4	1.4
下方投影面積	c m ²	1.5	2.1	1.9	1.7	1.6	2.1	1.9	1.7	1.6	2.0	1.8	1.7	1.6	1.9	1.8	1.7	1.6	1.5	
等価発光面積		c m ²	2.0	2.3	2.1	1.9	1.8	2.2	2.0	1.9	1.8	2.1	2.0	1.9	1.8	2.1	1.9	1.8	1.8	1.7
取付高さ	器具間隔最大限		2.5	2.3	2.2	2.1	2.0	2.3	2.2	2.0	1.9	2.2	2.1	2.0	1.9	2.2	2.1	2.0	1.9	1.8
	横方向 (A)	縦方向 (B)	3.0	2.4	2.3	2.2	2.1	2.4	2.2	2.1	2.0	2.3	2.2	2.1	2.0	2.2	2.1	2.1	2.0	1.9
H m	1.25 H m	1.26 H m	4.0	2.5	2.4	2.3	2.2	2.4	2.3	2.3	2.2	2.4	2.3	2.2	2.2	2.3	2.2	2.2	2.1	2.1
			5.0	2.5	2.4	2.4	2.3	2.5	2.4	2.3	2.3	2.4	2.4	2.3	2.2	2.4	2.3	2.2	2.2	2.1
			7.0	2.6	2.5	2.5	2.4	2.5	2.5	2.4	2.4	2.5	2.4	2.4	2.3	2.4	2.4	2.3	2.3	2.2
			10.0	2.6	2.6	2.5	2.5	2.6	2.5	2.5	2.5	2.5	2.5	2.4	2.4	2.5	2.4	2.4	2.4	2.3

