

# 屋内照明器具特性

品番 (品名)	L G W 8 5 1 0 2 Y F									
光源	LDA4L-H-E17/S/4 x1					440.0 lm				
管理番号	K0169572(0)DB1									
BZ分類	BZ5/0.7/BZ4									

器具効率	25%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	0%	反射率	10%				10%				10%				10%				0%				
下方光束	25%		床	10%				10%				10%				10%				0%			
室指数			照明率 ( X0.01 )																ZCM				
保守率	良	0.63	0.6	1.4	1.1	0.9	0.8	1.4	1.1	0.9	0.8	1.3	1.1	0.9	0.8	1.3	1.1	0.9	0.8	1.3	1.1	0.9	0.7
	中	0.6	0.8	1.7	1.4	1.2	1.1	1.7	1.4	1.2	1.1	1.6	1.4	1.2	1.1	1.6	1.4	1.2	1.1	1.5	1.3	1.2	1.0
	否	0.56	1.0	1.9	1.6	1.4	1.3	1.8	1.6	1.4	1.3	1.7	1.5	1.4	1.3	1.7	1.5	1.4	1.3	1.7	1.5	1.4	1.2
			1.25	2.0	1.8	1.6	1.5	2.0	1.8	1.6	1.5	1.9	1.7	1.6	1.4	1.9	1.8	1.7	1.5	1.8	1.7	1.5	1.4
下方投影面積	cm <sup>2</sup>	器具間隔最大限	1.5	2.1	1.9	1.7	1.6	2.1	1.9	1.7	1.6	2.0	1.8	1.7	1.6	2.0	1.8	1.7	1.6	1.9	1.8	1.7	1.5
等価発光面積	cm <sup>2</sup>		2.0	2.3	2.1	1.9	1.8	2.2	2.0	1.9	1.8	2.1	2.0	1.9	1.8	2.1	2.0	1.9	1.8	2.1	1.9	1.8	1.7
取付高さ	Hm		2.5	2.3	2.2	2.1	2.0	2.3	2.2	2.0	1.9	2.2	2.1	2.0	1.9	2.2	2.1	2.0	1.9	2.2	2.1	2.0	1.8
			3.0	2.4	2.3	2.2	2.1	2.4	2.2	2.1	2.0	2.3	2.2	2.1	2.0	2.2	2.1	2.0	1.9	2.2	2.1	2.0	1.9
		4.0	2.5	2.4	2.3	2.2	2.4	2.3	2.3	2.2	2.4	2.3	2.2	2.2	2.4	2.3	2.2	2.2	2.3	2.2	2.2	2.1	
		5.0	2.5	2.4	2.4	2.3	2.5	2.4	2.3	2.3	2.4	2.4	2.3	2.2	2.4	2.3	2.2	2.2	2.4	2.3	2.2	2.1	
		7.0	2.6	2.5	2.5	2.4	2.5	2.5	2.4	2.4	2.5	2.4	2.4	2.3	2.4	2.4	2.3	2.3	2.4	2.3	2.3	2.2	
		10.0	2.6	2.6	2.5	2.5	2.6	2.5	2.5	2.5	2.5	2.5	2.4	2.4	2.5	2.4	2.4	2.4	2.5	2.4	2.4	2.3	

