

屋内照明器具特性

| | | | | | | | | | | | | |
|---------|---------------------------------|-------------|------|---|--|--|---|--|--|---|--|--|
| 品番 (品名) | YYY66512K | | | | | | | | | | | |
| 光源 | LDA5L-D-G-E17/S/Z4 ×1 440.0 l m | | | | | | | | | | | |
| 管理番号 | K0186817(0)DB1 | | | | | | | | | | | |
| BZ分類 | BZ10 | | | | | | | | | | | |
| 器具効率 | 25% | 反射率 | 天井 | % | | | % | | | % | | |
| | 上方光束 13% | | 壁 | | | | | | | | | |
| | 下方光束 12% | | 床 | % | | | % | | | % | | |
| 室指数 | 照明率 (X0.01) ZCM | | | | | | | | | | | |
| 保守率 | 良 0.69 | 良 中 否 | 0.6 | | | | | | | | | |
| | 0.67 | | 0.8 | | | | | | | | | |
| | 0.63 | | 1.0 | | | | | | | | | |
| 下方投影面積 | c m ² | 1.25 | | | | | | | | | | |
| 等価発光面積 | c m ² | 1.5 | | | | | | | | | | |
| 取付高さ | 器具間隔最大限 | | 2.5 | | | | | | | | | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | | | | | | | | | |
| H m | 0.00 H m | 0.20 H m | 4.0 | | | | | | | | | |
| | | | 5.0 | | | | | | | | | |
| | | | 7.0 | | | | | | | | | |
| | | | 10.0 | | | | | | | | | |

