

屋内照明器具特性

品番 (品名)	L G W C 8 5 0 2 2 U				
光源	LDA4L-H-E17/S/4 ×1		440.0 lm		
管理番号	K0125231(1)DB1				
BZ分類	BZ10/0.9/BZ9				

器具効率	47%	天井	80%				70%				50%				30%				0%		
	上方光束		21%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	26%	床	10%				10%				10%				10%				0%		
室指数		照明率 (X0.01)																			ZCM
保守率	良	0.63	0.6	2.0	1.4	1.0	7	1.9	1.3	9	7	1.5	1.1	8	6	1.2	9	6	4	2	
	中	0.6	0.8	2.4	1.8	1.4	11	2.2	1.7	13	10	1.8	1.4	11	8	1.5	11	9	7	4	
	否	0.56	1.0	2.7	2.1	1.7	14	2.5	1.9	16	13	2.1	1.6	13	11	1.7	13	11	9	5	
			1.25	3.0	2.4	2.0	17	2.7	2.2	18	15	2.3	1.9	16	13	1.8	15	13	11	7	
下方投影面積		cm ²	1.5	3.2	2.6	2.2	19	2.9	2.4	2.1	18	2.4	2.1	18	15	2.0	17	15	13	8	
等価発光面積		cm ²	2.0	3.4	3.0	2.6	2.3	3.2	2.8	2.4	2.1	2.7	2.3	2.1	1.8	2.2	1.9	1.7	1.5	1.0	
取付高さ	器具間隔最大限		2.5	3.6	3.2	2.9	2.6	3.3	3.0	2.7	2.4	2.8	2.5	2.3	2.1	2.3	2.1	1.9	1.7	1.2	
	横方向 (A)	縦方向 (B)	3.0	3.8	3.4	3.1	2.8	3.5	3.1	2.9	2.6	2.9	2.7	2.4	2.2	2.4	2.2	2.1	1.9	1.3	
Hm	0.00Hm	2.57Hm	4.0	3.9	3.6	3.3	3.1	3.7	3.4	3.1	2.9	3.1	2.9	2.7	2.5	2.6	2.4	2.3	2.1	1.5	
			5.0	4.0	3.8	3.5	3.3	3.8	3.5	3.3	3.1	3.2	3.0	2.8	2.7	2.7	2.6	2.4	2.3	1.7	
			7.0	4.2	4.0	3.8	3.6	3.9	3.7	3.5	3.4	3.4	3.2	3.1	2.9	2.8	2.7	2.6	2.5	1.8	
			10.0	4.3	4.1	4.0	3.8	4.0	3.9	3.7	3.6	3.5	3.4	3.2	3.1	3.0	2.9	2.8	2.7	2.0	

