

屋内照明器具特性

品番 (品名)	LGWC85044AF														
光源	LDA4L-H-E17/S/4 ×1					440.0 lm									
管理番号	K0125233 (1) DB1														
BZ分類	BZ4/0.7/BZ5														

器具効率	77%	天井	80%				70%				50%				30%				0%	
	上方光束 9%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束 68%			壁	10%				10%				10%				10%			
室指数	照明率 (X0.01)															ZCM				
保守率	良 中 否 0.63 0.6 0.56	0.6	45	36	30	26	43	35	30	26	41	34	29	25	38	32	28	25	23	
		0.8	51	42	36	32	49	41	36	31	46	39	34	31	43	37	33	30	27	
		1.0	55	47	41	36	53	46	40	36	50	43	39	35	47	41	37	34	31	
		1.25	59	52	46	41	57	50	45	41	54	48	43	39	50	45	41	38	35	
		1.5	62	55	50	45	60	54	49	45	56	51	47	43	53	48	45	42	38	
下方投影面積 等価発光面積	cm ² cm ²	2.0	66	60	55	51	64	59	54	50	60	56	52	48	57	53	50	47	43	
		2.5	69	64	59	55	67	62	58	54	63	59	55	52	59	56	53	50	46	
取付 高さ	器具間隔最大限		3.0	71	66	62	58	69	64	61	57	65	61	58	55	61	58	55	53	49
	横方向 (A)	縦方向 (B)																		
H _m	1.14H _m	1.16H _m	4.0	73	69	66	63	71	68	64	62	67	64	61	59	63	61	59	57	53
			5.0	75	71	68	66	73	70	67	64	69	66	64	62	65	63	61	59	55
			7.0	76	74	72	69	74	72	70	68	70	69	67	65	67	65	64	62	58
			10.0	78	76	74	73	76	74	73	71	72	71	69	68	68	67	66	65	60

