

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 6 8 Y
光源	LDA4L-H-E17/S/4 ×1                      440.0 lm
管理番号	K0125729 (1) DB1
BZ分類	BZ10

器具効率	57 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	27 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	30 %		10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	2.4	1.7	1.2	9	2.2	1.5	1.1	8	1.8	1.3	9	6	1.4	1.0	7	5	2
	中	0.6	0.8	2.9	2.1	1.6	13	2.6	2.0	1.5	12	2.1	1.6	12	10	1.7	1.3	10	8	4
	否	0.56	1.0	3.2	2.5	2.0	16	2.9	2.3	1.8	15	2.4	1.9	15	12	1.9	1.5	12	10	5
			1.25	3.5	2.8	2.3	19	3.2	2.6	2.2	18	2.6	2.2	18	15	2.1	1.7	14	12	7
下方投影面積		cm <sup>2</sup>	1.5	3.8	3.1	2.6	2.2	3.4	2.9	2.4	2.1	2.8	2.4	2.0	1.7	2.3	1.9	1.6	1.4	9
等価発光面積		cm <sup>2</sup>	2.0	4.1	3.5	3.1	2.7	3.8	3.3	2.8	2.5	3.1	2.7	2.4	2.1	2.5	2.2	2.0	1.7	11
取付高さ	器具間隔最大限		2.5	4.3	3.8	3.4	3.0	4.0	3.5	3.1	2.8	3.3	3.0	2.7	2.4	2.7	2.4	2.2	2.0	13
	横方向 (A)	縦方向 (B)	3.0	4.5	4.0	3.6	3.3	4.1	3.7	3.4	3.1	3.5	3.1	2.9	2.6	2.8	2.6	2.4	2.2	14
H <sub>m</sub>	0.00H <sub>m</sub>	0.00H <sub>m</sub>	4.0	4.7	4.3	4.0	3.7	4.3	4.0	3.7	3.4	3.6	3.4	3.1	2.9	3.0	2.8	2.6	2.4	17
			5.0	4.8	4.5	4.2	3.9	4.5	4.2	3.9	3.7	3.8	3.5	3.3	3.1	3.1	2.9	2.8	2.6	18
			7.0	5.0	4.7	4.5	4.3	4.6	4.4	4.2	4.0	3.9	3.8	3.6	3.4	3.3	3.1	3.0	2.9	2.1
			10.0	5.1	4.9	4.7	4.6	4.8	4.6	4.4	4.3	4.1	3.9	3.8	3.7	3.4	3.3	3.2	3.1	2.2

