

|          |                                  |
|----------|----------------------------------|
| 屋内照明器具特性 |                                  |
| 品番 (品名)  | L G W C 8 5 0 7 6 S              |
| 光源       | LDA4L-H-E17/S/4 ×1      440.0 lm |
| 管理番号     | K0125801(1)DB1                   |
| BZ分類     | BZ10/0.7/BZ9                     |

|        |                 |         |               |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|--------|-----------------|---------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 32%             | 天井      | 80%           |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|        |                 | 壁       | 70            | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 14%             | 床       | 10%           |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 18%             | 室指数     | 照明率 ( X0.01 ) |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良 0.63          | 0.6     | 14            | 9  | 7  | 5  | 12  | 9  | 6  | 5  | 10  | 7  | 5  | 4  | 8   | 6  | 4  | 3  | 2   |    |
|        | 中 0.6           | 0.8     | 16            | 12 | 9  | 7  | 15  | 11 | 9  | 7  | 12  | 9  | 7  | 6  | 10  | 8  | 6  | 5  | 3   |    |
|        | 否 0.56          | 1.0     | 18            | 14 | 11 | 9  | 17  | 13 | 10 | 8  | 14  | 11 | 9  | 7  | 11  | 9  | 7  | 6  | 4   |    |
|        |                 | 1.25    | 20            | 16 | 13 | 11 | 18  | 15 | 12 | 10 | 15  | 13 | 10 | 9  | 12  | 10 | 9  | 7  | 5   |    |
| 下方投影面積 | cm <sup>2</sup> | 1.5     | 21            | 18 | 15 | 13 | 19  | 16 | 14 | 12 | 16  | 14 | 12 | 10 | 13  | 11 | 10 | 8  | 6   |    |
|        |                 | 2.0     | 23            | 20 | 17 | 15 | 21  | 18 | 16 | 14 | 18  | 16 | 14 | 12 | 15  | 13 | 12 | 10 | 7   |    |
| 取付高さ   | 器具間隔最大限         |         | 2.5           | 24 | 21 | 19 | 17  | 22 | 20 | 18 | 16  | 19 | 17 | 15 | 14  | 16 | 14 | 13 | 12  | 8  |
|        | 横方向 (A)         | 縦方向 (B) | 3.0           | 25 | 23 | 20 | 19  | 23 | 21 | 19 | 17  | 20 | 18 | 16 | 15  | 17 | 15 | 14 | 13  | 9  |
| Hm     | 0.00Hm          | 1.44Hm  | 4.0           | 26 | 24 | 22 | 21  | 24 | 23 | 21 | 19  | 21 | 19 | 18 | 17  | 18 | 16 | 15 | 14  | 10 |
|        |                 |         | 5.0           | 27 | 25 | 24 | 22  | 25 | 24 | 22 | 21  | 22 | 20 | 19 | 18  | 18 | 17 | 16 | 15  | 11 |
|        |                 |         | 7.0           | 28 | 27 | 25 | 24  | 26 | 25 | 24 | 23  | 23 | 22 | 21 | 20  | 19 | 18 | 18 | 17  | 13 |
|        |                 |         | 10.0          | 29 | 28 | 27 | 26  | 27 | 26 | 25 | 24  | 23 | 23 | 22 | 21  | 20 | 19 | 19 | 18  | 14 |

