

屋内照明器具特性

品番 (品名)	LGWC85076A															
光源	LDA4L-H-E17/S/4 x1 440.0lm															
管理番号	K0125730(1)DB1															
BZ分類	BZ10/0.7/BZ9															

器具効率	35%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	15%	室指数	照明率 (X0.01)																ZCM		
下方光束	20%																				
保守率	良 中 否	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
		0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
		0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
		0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	cm ²	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	15	10	8	6	5	4	3	2	1	0	
		1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	15	10	8	6	5	4	3	2	1	0	0	
等価発光面積	cm ²	2.0	2.5	3.0	4.0	5.0	7.0	10.0	15	10	8	6	5	4	3	2	1	0	0	0	
		2.5	3.0	4.0	5.0	7.0	10.0	15	10	8	6	5	4	3	2	1	0	0	0	0	
取付高さ	器具間隔最大限		Hm	0.00Hm	1.44Hm	Hm	1.44Hm	Hm	1.44Hm	Hm	1.44Hm	Hm	1.44Hm	Hm	1.44Hm	Hm	1.44Hm	Hm	1.44Hm	Hm	
	横方向 (A)	縦方向 (B)																			
Hm	0.00Hm	1.44Hm	Hm	0.00Hm	1.44Hm	Hm	0.00Hm	1.44Hm	Hm	0.00Hm	1.44Hm	Hm	0.00Hm	1.44Hm	Hm	0.00Hm	1.44Hm	Hm	0.00Hm	1.44Hm	

