

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 7 5 Y U
光源	L D A 4 L - H - E 1 7 / S / 4 × 1      4 4 0 . 0 l m
管理番号	K 0 1 2 5 9 7 2 ( 1 ) D B 1
B Z 分類	B Z 1 0 / 1 . 4 / B Z 9

器具効率	23 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	10 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	13 %		10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 ( X 0 . 0 1 )																Z C M	
保守率	良	0.63	0.6	1.0	7	5	3	9	6	4	3	7	5	4	2	6	4	3	2	1
	中	0.6	0.8	1.1	8	6	5	10	8	6	5	9	6	5	4	7	5	4	3	2
	否	0.56	1.0	1.3	10	8	6	12	9	7	6	10	8	6	5	8	6	5	4	2
			1.25	1.4	1.1	9	8	13	10	9	7	11	9	7	6	9	7	6	5	3
下方投影面積		cm <sup>2</sup>	1.5	1.5	1.2	1.0	9	14	11	10	8	11	10	8	7	9	8	7	6	4
等価発光面積		cm <sup>2</sup>	2.0	1.6	1.4	1.2	1.1	1.5	1.3	1.1	1.0	1.3	1.1	1.0	9	10	9	8	7	5
取付高さ	器具間隔最大限		2.5	1.7	1.5	1.4	1.2	1.6	1.4	1.3	1.1	1.3	1.2	1.1	1.0	1.1	1.0	9	8	6
	横方向 (A)	縦方向 (B)	3.0	1.8	1.6	1.5	1.3	1.7	1.5	1.4	1.2	1.4	1.3	1.2	1.1	1.2	1.1	1.0	9	6
H <sub>m</sub>	1.34H <sub>m</sub>	0.00H <sub>m</sub>	4.0	1.9	1.7	1.6	1.5	1.7	1.6	1.5	1.4	1.5	1.4	1.3	1.2	1.2	1.1	1.1	1.0	7
			5.0	1.9	1.8	1.7	1.6	1.8	1.7	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.2	1.1	1.1	8
			7.0	2.0	1.9	1.8	1.7	1.9	1.8	1.7	1.6	1.6	1.5	1.5	1.4	1.3	1.3	1.2	1.2	9
			10.0	2.1	2.0	1.9	1.8	1.9	1.8	1.8	1.7	1.7	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.0

