

屋内照明器具特性

品番 (品名)	L G W C 8 5 0 8 2 F	
光源	LDA4L-H-E17/S/4 ×1	440.0 lm
管理番号	K0172661(0)DR1	
BZ分類	BZ8	

器具効率	63%	天井	80%				70%				50%				30%				0%		
	上方光束		24%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		39%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	2.9	2.0	1.5	1.2	2.6	1.9	1.4	1.1	2.3	1.7	1.3	1.0	1.9	1.4	1.1	0.8	0.6	
	中	0.6	0.8	3.4	2.6	2.1	1.7	3.1	2.4	1.9	1.6	2.7	2.1	1.7	1.4	2.3	1.8	1.5	1.2	0.8	
	否	0.56	1.0	3.8	3.0	2.4	2.0	3.5	2.8	2.3	1.9	3.0	2.4	2.0	1.7	2.5	2.1	1.7	1.5	1.1	
			1.25	4.1	3.4	2.9	2.4	3.8	3.2	2.7	2.3	3.3	2.8	2.4	2.0	2.8	2.4	2.0	1.8	1.3	
下方投影面積	cm ²		1.5	4.4	3.7	3.2	2.8	4.1	3.5	3.0	2.6	3.5	3.0	2.6	2.3	3.0	2.6	2.3	2.0	1.5	
	等価発光面積		cm ²	2.0	4.7	4.1	3.7	3.3	4.4	3.9	3.4	3.1	3.8	3.4	3.0	2.7	3.2	2.9	2.6	2.4	1.8
取付高さ	器具間隔最大限		2.5	5.0	4.4	4.0	3.6	4.6	4.2	3.8	3.4	4.0	3.6	3.3	3.0	3.4	3.1	2.9	2.7	2.0	
	横方向 (A)	縦方向 (B)	3.0	5.1	4.7	4.3	3.9	4.8	4.4	4.0	3.7	4.2	3.8	3.5	3.3	3.6	3.3	3.1	2.9	2.2	
Hm	1.49Hm	1.57Hm	4.0	5.4	5.0	4.6	4.3	5.0	4.7	4.4	4.1	4.4	4.1	3.8	3.6	3.8	3.6	3.4	3.2	2.5	
			5.0	5.5	5.2	4.9	4.6	5.2	4.9	4.6	4.3	4.5	4.3	4.1	3.9	3.9	3.7	3.5	3.4	2.6	
			7.0	5.7	5.4	5.2	4.9	5.3	5.1	4.9	4.7	4.7	4.5	4.3	4.2	4.1	3.9	3.8	3.7	2.9	
			10.0	5.8	5.6	5.4	5.2	5.5	5.3	5.1	5.0	4.8	4.7	4.6	4.4	4.2	4.1	4.0	3.9	3.1	

