

# 屋内照明器具特性

品番 (品名)	LGWC85085F																													
光源	LDA4L-H-E17/S/4 ×1 440.0 1 m																													
管理番号	K0172661(0)DR1																													
BZ分類	BZ8																													
器具効率	63%	天井	80%				70%				50%				30%				0%											
	上方光束		24%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%									
	下方光束		39%		床	10%				10%				10%				10%				0%								
室指数	照明率 ( X0.01) ZCM																													
保守率	良	0.63	0.6	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0																	
	中	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	2.9	2.0	1.5	1.2	2.6	1.9	1.4	1.1	2.3	1.7	1.3	1.0	1.9	1.4	1.1	0.8	6
	否	0.56	0.6	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	3.4	2.6	2.1	1.7	3.1	2.4	1.9	1.6	2.7	2.1	1.7	1.4	2.3	1.8	1.5	1.2	8
															3.8	3.0	2.4	2.0	3.5	2.8	2.3	1.9	3.0	2.4	2.0	1.7	2.5	2.1	1.7	1.5
下方投影面積	cm <sup>2</sup>																													
等価発光面積	cm <sup>2</sup>																													
取付高さ	器具間隔最大限																													
	横方向 (A)	縦方向 (B)																												
H <sub>m</sub>	1.49H <sub>m</sub>	1.57H <sub>m</sub>	2.5	3.0	4.0	5.0	7.0	10.0	5.0	4.4	4.0	3.6	4.6	4.2	3.8	3.4	4.0	3.6	3.3	3.0	3.4	3.1	2.9	2.7	2.0					
			4.0	5.0	6.0	7.0	8.0	10.0	5.4	5.0	4.6	4.3	5.0	4.7	4.4	4.1	4.4	4.1	3.8	3.5	3.3	3.6	3.3	3.1	2.9	2.2				
			5.0	5.5	5.2	4.9	4.6	5.2	4.9	4.6	4.3	4.5	4.3	4.1	3.9	3.9	3.7	3.5	3.4	3.2	2.5									
			7.0	5.7	5.4	5.2	4.9	5.3	5.1	4.9	4.7	4.7	4.5	4.3	4.2	4.1	3.9	3.8	3.7	3.5	3.4	3.2	2.6							
			10.0	5.8	5.6	5.4	5.2	5.5	5.3	5.1	5.0	4.8	4.7	4.6	4.4	4.2	4.1	4.0	3.9	3.8	3.7	3.5	3.4	3.2	2.9	2.2				

