

# 屋内照明器具特性

品番 (品名)	L G W C 8 5 2 1 8 F									
光源	LDA4L-H-E17/S/4 ×1					440.0 lm				
管理番号	K0168589(0)DB1									
BZ分類	BZ7/0.7/BZ8/4.5/BZ7									

器具効率	54%	天井	80%				70%				50%				30%				0%		
	上方光束		13%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		41%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	c m <sup>2</sup>		1.25	3.6	2.9	2.4	2.0	3.4	2.8	2.3	2.0	3.0	2.5	2.1	1.8	2.6	2.2	1.9	1.6	1.3	
	等価発光面積		c m <sup>2</sup>	1.5	3.8	3.2	2.7	2.3	3.6	3.0	2.6	2.2	3.2	2.7	2.4	2.0	2.8	2.4	2.1	1.9	1.5
取付高さ	器具間隔最大限		2.5	4.4	3.9	3.5	3.1	4.1	3.7	3.3	3.0	3.7	3.3	3.0	2.7	3.3	3.0	2.8	2.5	2.1	
	横方向 (A)	縦方向 (B)	3.0	4.5	4.1	3.7	3.4	4.3	3.9	3.6	3.2	3.9	3.5	3.2	3.0	3.5	3.2	3.0	2.7	2.3	
H m	0.65 H m	0.66 H m	4.0	4.7	4.4	4.1	3.8	4.5	4.2	3.9	3.6	4.1	3.8	3.6	3.3	3.7	3.5	3.3	3.1	2.6	
			5.0	4.9	4.6	4.3	4.0	4.7	4.4	4.1	3.9	4.2	4.0	3.8	3.6	3.8	3.6	3.5	3.3	2.8	
			7.0	5.1	4.8	4.6	4.4	4.8	4.6	4.4	4.2	4.4	4.2	4.1	3.9	4.0	3.9	3.7	3.6	3.1	
			10.0	5.2	5.0	4.8	4.7	5.0	4.8	4.7	4.5	4.6	4.4	4.3	4.2	4.2	4.0	3.9	3.8	3.3	

