

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 6 8 A
光源	LDA4L-H-E17/S/4 x1 440.0 lm
管理番号	K0125729 (1) DB1
BZ分類	BZ10

器具効率	57%	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
上方光束	27%	床	10%				10%				10%				10%				0%
下方光束	30%		10%				10%				10%				10%				0%
器具効率		室指数	照明率 (X0.01)																ZCM
保守率	良 0.63	0.6	2.4	1.7	1.2	0.9	2.2	1.5	1.1	0.8	1.8	1.3	0.9	0.6	1.4	1.0	0.7	0.5	0.2
	中 0.6	0.8	2.9	2.1	1.6	1.3	2.6	2.0	1.5	1.2	2.1	1.6	1.2	1.0	1.7	1.3	1.0	0.8	0.4
	否 0.56	1.0	3.2	2.5	2.0	1.6	2.9	2.3	1.8	1.5	2.4	1.9	1.5	1.2	1.9	1.5	1.2	1.0	0.5
		1.25	3.5	2.8	2.3	1.9	3.2	2.6	2.2	1.8	2.6	2.2	1.8	1.5	2.1	1.7	1.4	1.2	0.7
下方投影面積	cm ²	1.5	3.8	3.1	2.6	2.2	3.4	2.9	2.4	2.1	2.8	2.4	2.0	1.7	2.3	1.9	1.6	1.4	0.9
		2.0	4.1	3.5	3.1	2.7	3.8	3.3	2.8	2.5	3.1	2.7	2.4	2.1	2.5	2.2	2.0	1.7	1.1
取付高さ	器具間隔最大限		2.5	4.3	3.8	3.4	3.0	4.0	3.5	3.1	2.8	3.3	3.0	2.7	2.4	2.7	2.4	2.0	1.3
	横方向 (A)	縦方向 (B)	3.0	4.5	4.0	3.6	3.3	4.1	3.7	3.4	3.1	3.5	3.1	2.9	2.6	2.8	2.6	2.4	1.4
H _m	0.00H _m	0.00H _m	4.0	4.7	4.3	4.0	3.7	4.3	4.0	3.7	3.4	3.6	3.4	3.1	2.9	3.0	2.8	2.6	1.7
			5.0	4.8	4.5	4.2	3.9	4.5	4.2	3.9	3.7	3.8	3.5	3.3	3.1	3.1	2.9	2.8	1.8
			7.0	5.0	4.7	4.5	4.3	4.6	4.4	4.2	4.0	3.9	3.8	3.6	3.4	3.3	3.1	3.0	2.1
			10.0	5.1	4.9	4.7	4.6	4.8	4.6	4.4	4.3	4.1	3.9	3.8	3.7	3.4	3.3	3.2	2.2

