

# 屋内照明器具特性

|         |                             |  |  |  |  |           |  |  |  |  |
|---------|-----------------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | LGB10854                    |  |  |  |  |           |  |  |  |  |
| 光源      | LLD4000LCE1 ×1              |  |  |  |  | 845.0 1 m |  |  |  |  |
| 管理番号    | K0190088 (1) DR 1           |  |  |  |  |           |  |  |  |  |
| BZ分類    | BZ3 / 0.7 / BZ2 / 1.8 / BZ3 |  |  |  |  |           |  |  |  |  |

|        |                  |          |               |     |      |     |      |     |      |     |      |     |      |     |      |     |      |     |     |     |     |
|--------|------------------|----------|---------------|-----|------|-----|------|-----|------|-----|------|-----|------|-----|------|-----|------|-----|-----|-----|-----|
| 器具効率   | 65 %             | 天井       | 80 %          |     |      |     | 70 % |     |      |     | 50 % |     |      |     | 30 % |     |      |     | 0 % |     |     |
|        |                  |          | 反射率           | 壁   | 70   | 50  | 30   | 10  | 70   | 50  | 30   | 10  | 70   | 50  | 30   | 10  | 70   | 50  | 30  | 10  | 0 % |
|        |                  |          |               | 床   | 10 % |     |      |     | 10 % |     |      |     | 10 % |     |      |     | 10 % |     |     |     | 0 % |
| 上方光束   | 0 %              | 室指数      | 照明率 ( X0.01 ) |     |      |     |      |     |      |     |      |     |      |     |      |     |      |     | ZCM |     |     |
| 下方光束   | 65 %             |          |               |     |      |     |      |     |      |     |      |     |      |     |      |     |      |     |     |     |     |
| 保守率    | 良<br>中<br>否      | 0.67     | 0.6           | 4.2 | 3.6  | 3.1 | 2.8  | 4.2 | 3.5  | 3.1 | 2.8  | 4.0 | 3.5  | 3.1 | 2.8  | 3.9 | 3.4  | 3.1 | 2.8 | 2.7 |     |
|        |                  | 0.63     | 0.8           | 4.9 | 4.3  | 3.9 | 3.6  | 4.8 | 4.2  | 3.9 | 3.6  | 4.6 | 4.2  | 3.8 | 3.5  | 4.5 | 4.1  | 3.8 | 3.5 | 3.4 |     |
|        |                  | 0.56     | 1.0           | 5.3 | 4.7  | 4.4 | 4.1  | 5.2 | 4.7  | 4.3 | 4.1  | 5.0 | 4.6  | 4.3 | 4.0  | 4.9 | 4.5  | 4.2 | 4.0 | 3.9 |     |
|        |                  |          | 1.25          | 5.6 | 5.1  | 4.8 | 4.5  | 5.5 | 5.1  | 4.8 | 4.5  | 5.4 | 5.0  | 4.7 | 4.4  | 5.2 | 4.9  | 4.6 | 4.4 | 4.3 |     |
| 下方投影面積 | c m <sup>2</sup> | 1.5      | 5.8           | 5.4 | 5.1  | 4.8 | 5.8  | 5.4 | 5.0  | 4.8 | 5.6  | 5.2 | 5.0  | 4.7 | 5.4  | 5.1 | 4.9  | 4.7 | 4.6 |     |     |
|        |                  | 2.0      | 6.1           | 5.8 | 5.5  | 5.2 | 6.0  | 5.7 | 5.4  | 5.2 | 5.9  | 5.6 | 5.4  | 5.2 | 5.7  | 5.5 | 5.3  | 5.1 | 5.0 |     |     |
| 取付高さ   | 器具間隔最大限          |          | 2.5           | 6.3 | 6.0  | 5.8 | 5.5  | 6.2 | 5.9  | 5.7 | 5.5  | 6.0 | 5.8  | 5.6 | 5.4  | 5.9 | 5.7  | 5.5 | 5.4 | 5.2 |     |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0           | 6.4 | 6.2  | 5.9 | 5.7  | 6.3 | 6.1  | 5.9 | 5.7  | 6.2 | 6.0  | 5.8 | 5.6  | 6.0 | 5.8  | 5.7 | 5.6 | 5.4 |     |
| H m    | 1.32 H m         | 1.32 H m | 4.0           | 6.6 | 6.4  | 6.2 | 6.0  | 6.5 | 6.3  | 6.1 | 6.0  | 6.3 | 6.2  | 6.0 | 5.9  | 6.2 | 6.0  | 5.9 | 5.8 | 5.6 |     |
|        |                  |          | 5.0           | 6.7 | 6.5  | 6.3 | 6.2  | 6.6 | 6.4  | 6.3 | 6.2  | 6.4 | 6.3  | 6.2 | 6.1  | 6.3 | 6.1  | 6.0 | 6.0 | 5.8 | 5.8 |
|        |                  |          | 7.0           | 6.8 | 6.6  | 6.5 | 6.4  | 6.7 | 6.6  | 6.5 | 6.4  | 6.5 | 6.4  | 6.3 | 6.2  | 6.4 | 6.3  | 6.2 | 6.1 | 6.0 |     |
|        |                  |          | 10.0          | 6.8 | 6.8  | 6.7 | 6.6  | 6.8 | 6.7  | 6.6 | 6.5  | 6.6 | 6.5  | 6.5 | 6.4  | 6.4 | 6.4  | 6.3 | 6.3 | 6.1 |     |

