

屋内照明器具特性

品番 (品名)	LGB10854														
光源	LLD40001CQ1 ×1 845.0 lm														
管理番号	K0190098 (1) DR1														
BZ分類	BZ3/0.7/BZ2/3.5/BZ3/6.0/BZ2														

器具効率	63%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)																ZCM		
下方光束	63%																				
保守率	良 0.67 中 0.63 否 0.56	0.6	41	35	31	28	40	34	30	28	39	34	30	28	38	33	30	28	27		
		0.8	47	42	38	35	47	41	37	35	45	40	37	35	44	40	37	34	33		
		1.0	51	46	42	40	50	46	42	39	49	45	42	39	48	44	41	39	38		
		1.25	54	50	46	44	54	49	46	44	52	48	46	43	51	48	45	43	42		
下方投影面積	c m ²	1.5	57	52	49	47	56	52	49	47	54	51	48	46	53	50	48	46	45		
		2.0	59	56	53	51	58	55	53	51	57	54	52	50	55	53	51	50	48		
取付高さ	器具間隔最大限		2.5	61	58	56	54	60	58	55	53	59	56	55	53	57	55	54	52	51	
	横方向 (A)	縦方向 (B)	3.0	62	60	58	56	61	59	57	55	60	58	56	55	58	57	55	54	53	
H m	1.31H m	1.31H m	4.0	64	62	60	59	63	61	59	58	61	60	58	57	60	59	57	56	55	
			5.0	64	63	61	60	64	62	61	60	62	61	60	59	61	60	59	58	56	
			7.0	65	64	63	62	65	64	63	62	63	62	61	61	62	61	60	58		
			10.0	66	65	65	64	65	65	64	63	64	63	63	62	62	62	61	61	59	

