

屋内照明器具特性

品番 (品名)	LGB16154				
光源	LLD2000LCE1 x1 531.0lm				
管理番号	K0190090(1)DR1				
BZ分類	BZ3/0.7/BZ2/1.8/BZ3				

器具効率	70%	天井	80%				70%				50%				30%				0%		
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
																				壁	床
上方光束	1%		10%				10%				10%				10%				0%		
下方光束	69%		10%				10%				10%				10%				0%		
保守率	良中否	室指数	照明率 (X0.01) ZCM																		
	0.67	0.6	45	38	34	30	45	38	33	30	43	37	33	30	42	36	33	30	29		
	0.63	0.8	52	46	41	38	51	45	41	38	50	45	41	38	48	44	40	38	37		
	0.56	1.0	57	51	47	44	56	50	46	43	54	49	46	43	52	48	45	43	41		
下方投影面積	cm^2	1.25	60	55	51	48	59	54	51	48	57	53	50	48	56	52	50	47	46		
等価発光面積	cm^2	1.5	63	58	54	51	62	57	54	51	60	56	53	51	58	55	52	50	49		
取付高さ	器具間隔最大限		2.5	68	64	62	59	67	64	61	59	65	62	60	58	63	61	59	57	56	
	横方向 (A)	縦方向 (B)	3.0	69	66	64	62	68	65	63	61	66	64	62	60	64	62	61	59	58	
Hm	1.31Hm	1.31Hm	4.0	70	68	66	65	69	67	66	64	68	66	64	63	66	65	63	62	60	
			5.0	71	70	68	66	70	69	67	66	69	67	66	65	67	66	65	64	62	
			7.0	72	71	70	69	72	70	69	68	70	69	68	67	68	67	66	66	64	
			10.0	73	72	71	71	72	72	71	70	71	70	69	69	69	68	68	67	65	

