

# 屋内照明器具特性

品番 (品名)	LGB16154				
光源	LLD4000MLCE1 ×1		845.0 l m		
管理番号	K0190092 (1) DR 1				
BZ分類	BZ3 / 0.9 / BZ2 / 1.8 / BZ3				

器具効率	64 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	1 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	63 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	4.2	3.5	3.1	2.8	4.1	3.5	3.1	2.8	3.9	3.4	3.0	2.8	3.8	3.3	3.0	2.8	2.6
	中	0.63	0.8	4.8	4.2	3.8	3.5	4.7	4.2	3.8	3.5	4.6	4.1	3.7	3.5	4.4	4.0	3.7	3.5	3.3
	否	0.56	1.0	5.2	4.7	4.3	4.0	5.1	4.6	4.2	4.0	4.9	4.5	4.2	3.9	4.8	4.4	4.1	3.9	3.8
			1.25	5.5	5.0	4.7	4.4	5.4	5.0	4.7	4.4	5.3	4.9	4.6	4.4	5.1	4.8	4.5	4.3	4.2
下方投影面積		cm <sup>2</sup>	1.5	5.7	5.3	5.0	4.7	5.6	5.3	4.9	4.7	5.5	5.1	4.9	4.6	5.3	5.0	4.8	4.6	4.5
等価発光面積		cm <sup>2</sup>	2.0	6.0	5.7	5.4	5.1	5.9	5.6	5.3	5.1	5.8	5.5	5.3	5.1	5.6	5.4	5.2	5.0	4.9
取付高さ	器具間隔最大限		2.5	6.2	5.9	5.6	5.4	6.1	5.8	5.6	5.4	5.9	5.7	5.5	5.3	5.8	5.6	5.4	5.3	5.1
	横方向 (A)	縦方向 (B)	3.0	6.3	6.1	5.8	5.6	6.2	6.0	5.8	5.6	6.0	5.9	5.7	5.5	5.9	5.7	5.6	5.4	5.3
Hm	1.32 Hm	1.32 Hm	4.0	6.5	6.3	6.1	5.9	6.4	6.2	6.0	5.9	6.2	6.0	5.9	5.8	6.0	5.9	5.8	5.7	5.5
			5.0	6.5	6.4	6.2	6.1	6.5	6.3	6.2	6.0	6.3	6.2	6.0	5.9	6.1	6.0	5.9	5.8	5.7
			7.0	6.6	6.5	6.4	6.3	6.6	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.2	6.2	6.1	6.0	5.8
			10.0	6.7	6.6	6.5	6.5	6.6	6.6	6.5	6.4	6.5	6.4	6.3	6.3	6.3	6.3	6.2	6.2	6.0

