

# 屋内照明器具特性

品番 (品名)	LGB10855	
光源	LLD4000LCE1 ×1	845.0 1 m
管理番号	K0190088 (1) DR 1	
BZ分類	BZ3 / 0.7 / BZ2 / 1.8 / BZ3	

器具効率	65 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	65 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.67	0.6	4.2	3.6	3.1	2.8	4.2	3.5	3.1	2.8	4.0	3.5	3.1	2.8	3.9	3.4	3.1	2.8	2.7
	中	0.63	0.8	4.9	4.3	3.9	3.6	4.8	4.2	3.9	3.6	4.6	4.2	3.8	3.5	4.5	4.1	3.8	3.5	3.4
	否	0.56	1.0	5.3	4.7	4.4	4.1	5.2	4.7	4.3	4.1	5.0	4.6	4.3	4.0	4.9	4.5	4.2	4.0	3.9
			1.25	5.6	5.1	4.8	4.5	5.5	5.1	4.8	4.5	5.4	5.0	4.7	4.4	5.2	4.9	4.6	4.4	4.3
下方投影面積	cm <sup>2</sup>		1.5	5.8	5.4	5.1	4.8	5.8	5.4	5.0	4.8	5.6	5.2	5.0	4.7	5.4	5.1	4.9	4.7	4.6
等価発光面積	cm <sup>2</sup>		2.0	6.1	5.8	5.5	5.2	6.0	5.7	5.4	5.2	5.9	5.6	5.4	5.2	5.7	5.5	5.3	5.1	5.0
取付高さ	器具間隔最大限		2.5	6.3	6.0	5.8	5.5	6.2	5.9	5.7	5.5	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.4	5.2
	横方向 (A)	縦方向 (B)	3.0	6.4	6.2	5.9	5.7	6.3	6.1	5.9	5.7	6.2	6.0	5.8	5.6	6.0	5.8	5.7	5.6	5.4
Hm	1.32 Hm	1.32 Hm	4.0	6.6	6.4	6.2	6.0	6.5	6.3	6.1	6.0	6.3	6.2	6.0	5.9	6.2	6.0	5.9	5.8	5.6
			5.0	6.7	6.5	6.3	6.2	6.6	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.3	6.1	6.0	6.0	5.8
			7.0	6.8	6.6	6.5	6.4	6.7	6.6	6.5	6.4	6.5	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.0
			10.0	6.8	6.8	6.7	6.6	6.8	6.7	6.6	6.5	6.6	6.5	6.5	6.4	6.4	6.4	6.3	6.3	6.1

