

屋内照明器具特性	
品番(品名)	LGB10855
光源	LLD4000MLCE1 ×1 845.0 l m
管理番号	K0190092(1)DR1
BZ分類	BZ3/0.9/BZ2/1.8/BZ3

器具効率	64%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	1%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	63%																																																						
保守率	良 中 否	0.67	0.6	4.2	3.5	3.1	2.8	4.1	3.5	3.1	2.8	3.9	3.4	3.0	2.8	3.8	3.3	3.0	2.8	2.6																																			
		0.63	0.8	4.8	4.2	3.8	3.5	4.7	4.2	3.8	3.5	4.6	4.1	3.7	3.5	4.4	4.0	3.7	3.5	3.3																																			
		0.56	1.0	5.2	4.7	4.3	4.0	5.1	4.6	4.2	4.0	4.9	4.5	4.2	3.9	4.8	4.4	4.1	3.9	3.8																																			
			1.25	5.5	5.0	4.7	4.4	5.4	5.0	4.7	4.4	5.3	4.9	4.6	4.4	5.1	4.8	4.5	4.3	4.2																																			
下方投影面積	c m ²	1.5	5.7	5.3	5.0	4.7	5.6	5.3	4.9	4.7	5.5	5.1	4.9	4.6	5.3	5.0	4.8	4.6	4.5																																				
		2.0	6.0	5.7	5.4	5.1	5.9	5.6	5.3	5.1	5.8	5.5	5.3	5.1	5.6	5.4	5.2	5.0	4.9																																				
		2.5	6.2	5.9	5.6	5.4	6.1	5.8	5.6	5.4	5.9	5.7	5.5	5.3	5.8	5.6	5.4	5.3	5.1																																				
取付高さ	器具間隔最大限		3.0	6.3	6.1	5.8	5.6	6.2	6.0	5.8	5.6	6.0	5.9	5.7	5.5	5.9	5.7	5.6	5.4	5.3																																			
	横方向(A)	縦方向(B)																																																					
H m	1.32 H m	1.32 H m	4.0	6.5	6.3	6.1	5.9	6.4	6.2	6.0	5.9	6.2	6.0	5.9	5.8	6.0	5.9	5.8	5.7	5.5																																			
			5.0	6.5	6.4	6.2	6.1	6.5	6.3	6.2	6.0	6.3	6.2	6.0	5.9	6.1	6.0	5.9	5.8	5.7																																			
			7.0	6.6	6.5	6.4	6.3	6.6	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.2	6.2	6.1	6.0	5.8																																			
			10.0	6.7	6.6	6.5	6.5	6.6	6.6	6.5	6.4	6.5	6.4	6.3	6.3	6.3	6.3	6.2	6.2	6.0																																			

