

屋内照明器具特性	
品番 (品名)	LGB10855
光源	LLD40001CQ1 ×1 845.0 1 m
管理番号	K0190098 (1) DR 1
BZ分類	BZ3/0.7/BZ2/3.5/BZ3/6.0/BZ2

器具効率	63 %	天井	80 %				70 %				50 %				30 %				0 %																														
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																														
		床	10 %				10 %				10 %				10 %				0 %																														
上方光束	0 %	室指数																照明率 (X0.01)																ZCM															
下方光束	63 %																																																
保守率	良	0.67	0.6	41	35	31	28	40	34	30	28	39	34	30	28	38	33	30	28	27																													
	中	0.63	0.8	47	42	38	35	47	41	37	35	45	40	37	35	44	40	37	34	33																													
	否	0.56	1.0	51	46	42	40	50	46	42	39	49	45	42	39	48	44	41	39	38																													
			1.25	54	50	46	44	54	49	46	44	52	48	46	43	51	48	45	43	42																													
下方投影面積			1.5	57	52	49	47	56	52	49	47	54	51	48	46	53	50	48	46	45																													
			2.0	59	56	53	51	58	55	53	51	57	54	52	50	55	53	51	50	48																													
取付高さ	器具間隔最大限		2.5	61	58	56	54	60	58	55	53	59	56	55	53	57	55	54	52	51																													
	横方向 (A)	縦方向 (B)	3.0	62	60	58	56	61	59	57	55	60	58	56	55	58	57	55	54	53																													
Hm	1.31Hm	1.31Hm	4.0	64	62	60	59	63	61	59	58	61	60	58	57	60	59	57	56	55																													
			5.0	64	63	61	60	64	62	61	60	62	61	60	59	61	60	59	58	56																													
			7.0	65	64	63	62	65	64	63	62	63	62	61	61	62	61	60	60	58																													
			10.0	66	65	65	64	65	65	64	63	64	63	63	62	62	62	61	61	59																													

