

屋内照明器具特性

品番 (品名) **LGB10855**

光源 **LLD2020LCT1 ×1** **460.0 1m**

管理番号 **K0190112 (1) DR1**

BZ分類 **BZ1**

器具効率	90 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	90 %		壁	10 %				10 %				10 %				10 %				
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	77	72	69	66	76	72	69	66	75	71	68	66	74	71	68	66	65	
	中 0.63	0.8	82	78	75	73	82	78	75	72	80	77	74	72	79	76	74	72	71	
	否 0.56	1.0	86	82	79	77	85	81	78	76	83	80	78	76	82	79	77	76	75	
下方投影面積	c m ²	1.25	88	85	82	80	87	84	82	80	86	83	81	79	84	82	80	79	78	
		1.5	90	87	84	82	89	86	84	82	87	85	83	82	86	84	82	81	80	
等価発光面積	c m ²	2.0	92	89	87	86	91	89	87	85	89	87	86	85	88	86	85	84	82	
		2.5	93	91	89	88	92	90	89	87	90	89	88	86	89	88	86	85	84	
取付高さ	器具間隔最大限		3.0	94	92	91	89	93	91	90	89	91	90	89	88	90	88	88	87	85
H m	0.41 H m	0.41 H m	4.0	95	94	92	91	94	93	92	91	92	91	90	89	90	90	89	88	86
			5.0	95	94	93	93	95	94	93	92	93	92	91	90	91	90	90	90	89
			7.0	96	95	95	94	95	94	94	93	93	93	92	92	91	91	91	90	88
			10.0	97	96	96	95	96	95	95	94	94	93	93	93	92	92	91	91	89

