

屋内照明器具特性	
品番 (品名)	LGB16155
光源	LLD4000MLCE1 ×1 845.0 lm
管理番号	K0190092 (1) DR1
BZ分類	BZ3/0.9/BZ2/1.8/BZ3

器具効率		64 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 ( X0.01 )																ZCM
保守率		良 中 否	0.67	0.6	42	35	31	28	41	35	31	28	39	34	30	28	38	33	30	28	26
			0.63	0.8	48	42	38	35	47	42	38	35	46	41	37	35	44	40	37	35	33
			0.56	1.0	52	47	43	40	51	46	42	40	49	45	42	39	48	44	41	39	38
				1.25	55	50	47	44	54	50	47	44	53	49	46	44	51	48	45	43	42
下方投影面積		cm <sup>2</sup>		1.5	57	53	50	47	56	53	49	47	55	51	49	46	53	50	48	46	45
			等価発光面積	cm <sup>2</sup>	2.0	60	57	54	51	59	56	53	51	58	55	53	51	56	54	52	50
取付 高さ	器具間隔最大限			2.5	62	59	56	54	61	58	56	54	59	57	55	53	58	56	54	53	51
	横方向 ( A )			縦方向 ( B )		3.0	63	61	58	56	62	60	58	56	60	59	57	55	59	57	56
H m	1.32 H m		1.32 H m	4.0	65	63	61	59	64	62	60	59	62	60	59	58	60	59	58	57	55
				5.0	65	64	62	61	65	63	62	60	63	62	60	59	61	60	59	58	57
				7.0	66	65	64	63	66	64	63	62	64	63	62	61	62	62	61	60	58
				10.0	67	66	65	65	66	66	65	64	65	64	63	63	63	63	62	62	60

