

屋内照明器具特性	
品番 (品名)	FTKW11820K13 (JOUJI)
光源	LDA8L-G-E17/Z60/S/W ×1 760.0 1m
管理番号	K0151707 (2) DR1
BZ分類	BZ10/0.9/BZ9

器具効率	19%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	9%	床	10%				10%				10%				10%				0%	
下方光束	10%		10%				10%				10%				10%				0%	
室指数		照明率 (X0.01)																ZCM		
保守率	良	0.63	0.6	8	6	4	3	7	5	4	3	6	4	3	2	5	3	2	2	1
	中	0.6	0.8	10	7	5	4	9	7	5	4	7	5	4	3	6	4	3	3	1
	否	0.56	1.0	11	8	7	5	10	8	6	5	8	6	5	4	6	5	4	3	2
			1.25	12	10	8	7	11	9	7	6	9	7	6	5	7	6	5	4	2
下方投影面積		cm ²	1.5	13	10	9	8	12	10	8	7	10	8	7	6	8	7	6	5	3
等価発光面積		cm ²	2.0	14	12	10	9	13	11	10	8	10	9	8	7	8	7	7	6	4
取付高さ	器具間隔最大限		2.5	14	13	11	10	13	12	11	9	11	10	9	8	9	8	7	7	4
	横方向 (A)	縦方向 (B)	3.0	15	13	12	11	14	12	11	10	12	11	10	9	10	9	8	7	5
Hm	0.00Hm	2.34Hm	4.0	16	14	13	12	15	13	12	11	12	11	11	10	10	9	9	6	
			5.0	16	15	14	13	15	14	13	12	13	12	11	11	10	9	9	6	
			7.0	17	16	15	14	16	15	14	13	13	13	12	12	11	11	10	7	
			10.0	17	17	16	15	16	15	15	14	14	13	13	12	12	11	11	10	8

