

屋内照明器具特性

品番 (品名)	XED3 1 2 1 L	
光源	LLD3 0 2 0 LCT1 × 1	795.0 l m
管理番号	K0190488 (0) DR 1	
B Z 分類	B Z 1	

器具効率	68 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	68 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X 0.01)																			Z C M
保守率	良 0.63	0.6	0.6	56	51	49	47	55	51	48	47	54	51	48	46	53	50	48	46	46
	中 0.6		0.8	60	56	53	51	59	56	53	51	58	55	53	51	57	55	53	51	50
	否 0.56		1.0	63	59	56	55	62	59	56	54	61	58	56	54	60	57	55	54	53
下方投影面積 等価発光面積	c m ²	c m ²	1.25	65	62	59	57	64	61	59	57	63	60	58	57	62	60	58	57	56
			1.5	66	63	61	60	65	63	61	59	64	62	60	59	63	61	60	58	57
取付高さ	器具間隔最大限		2.5	69	67	66	64	68	67	65	64	67	65	64	63	66	64	63	62	61
	横方向 (A)	縦方向 (B)	3.0	70	68	67	65	69	67	66	65	68	66	65	64	66	65	64	63	62
H m	0.41 H m	0.41 H m	4.0	71	69	68	67	70	69	68	67	68	67	67	66	67	66	65	65	63
			5.0	71	70	69	68	70	69	69	68	69	68	67	67	68	67	66	66	64
			7.0	72	71	70	69	71	70	70	69	69	69	68	68	68	68	67	67	65
			10.0	72	72	71	70	71	71	70	70	70	69	69	69	68	68	68	67	66

