

屋内照明器具特性

品番 (品名)	XND9 9 8 6 S WZ	
光源	LED4000_80_12030 x1	12030.0 1m
管理番号	K0188506 (0) DB 1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	
上方光束	0%	壁	照明率 (X0.01)																ZCM
下方光束	100%	床	照明率 (X0.01)																ZCM
保守率	良	室指数	照明率 (X0.01)																ZCM
	中		照明率 (X0.01)																ZCM
	否		照明率 (X0.01)																ZCM
	0.76		照明率 (X0.01)																ZCM
下方投影面積	cm ²	1.25	照明率 (X0.01)																ZCM
		1.5	照明率 (X0.01)																ZCM
等価発光面積	cm ²	2.0	照明率 (X0.01)																ZCM
		2.5	照明率 (X0.01)																ZCM
取付高さ	器具間隔最大限		照明率 (X0.01)																ZCM
	Hm	0.72Hm	照明率 (X0.01)																ZCM
Hm	0.72Hm	0.72Hm	照明率 (X0.01)																ZCM
	4.0		照明率 (X0.01)																ZCM
Hm	0.72Hm	0.72Hm	照明率 (X0.01)																ZCM
	5.0		照明率 (X0.01)																ZCM
Hm	0.72Hm	0.72Hm	照明率 (X0.01)																ZCM
	7.0		照明率 (X0.01)																ZCM
Hm	0.72Hm	0.72Hm	照明率 (X0.01)																ZCM
	10.0		照明率 (X0.01)																ZCM

