

| | |
|----------|-----------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | XF Y6 6 0 0 C |
| 光源 | LDL40S.N/29/38(3800A) ×6 3800.0lm |
| 管理番号 | K0125273(0)DC1 |
| BZ分類 | BZ5 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|-----------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率 | 61% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 1% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 60% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.86 | 0.6 | 3.4 | 2.7 | 2.2 | 1.9 | 3.4 | 2.7 | 2.2 | 1.9 | 3.2 | 2.6 | 2.2 | 1.9 | 3.1 | 2.5 | 2.1 | 1.9 | 1.8 |
| | 中 | 0.81 | 0.8 | 4.0 | 3.3 | 2.9 | 2.5 | 3.9 | 3.3 | 2.8 | 2.5 | 3.8 | 3.2 | 2.8 | 2.5 | 3.6 | 3.1 | 2.8 | 2.5 | 2.4 |
| | 否 | 0.76 | 1.0 | 4.4 | 3.8 | 3.3 | 3.0 | 4.3 | 3.7 | 3.3 | 3.0 | 4.2 | 3.6 | 3.2 | 2.9 | 4.0 | 3.5 | 3.2 | 2.9 | 2.8 |
| | | | 1.25 | 4.8 | 4.2 | 3.8 | 3.4 | 4.7 | 4.1 | 3.7 | 3.4 | 4.5 | 4.0 | 3.7 | 3.4 | 4.3 | 3.9 | 3.6 | 3.3 | 3.2 |
| 下方投影面積 | | cm ² | 1.5 | 5.0 | 4.5 | 4.1 | 3.8 | 4.9 | 4.4 | 4.1 | 3.7 | 4.7 | 4.3 | 4.0 | 3.7 | 4.6 | 4.2 | 3.9 | 3.7 | 3.5 |
| 等価発光面積 | | cm ² | 2.0 | 5.4 | 4.9 | 4.6 | 4.3 | 5.3 | 4.9 | 4.5 | 4.2 | 5.1 | 4.7 | 4.4 | 4.2 | 4.9 | 4.6 | 4.3 | 4.1 | 4.0 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 5.6 | 5.2 | 4.9 | 4.6 | 5.5 | 5.1 | 4.8 | 4.6 | 5.3 | 5.0 | 4.7 | 4.5 | 5.1 | 4.9 | 4.6 | 4.4 | 4.3 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 5.7 | 5.4 | 5.1 | 4.9 | 5.6 | 5.3 | 5.1 | 4.8 | 5.5 | 5.2 | 5.0 | 4.7 | 5.3 | 5.1 | 4.9 | 4.7 | 4.5 |
| 1.5m | 2.32m | 2.28m | 4.0 | 5.9 | 5.7 | 5.4 | 5.2 | 5.8 | 5.6 | 5.4 | 5.2 | 5.6 | 5.4 | 5.2 | 5.1 | 5.5 | 5.3 | 5.1 | 5.0 | 4.8 |
| 2 | 2.85 | 2.79 | 5.0 | 6.0 | 5.8 | 5.6 | 5.4 | 5.9 | 5.7 | 5.5 | 5.4 | 5.8 | 5.6 | 5.4 | 5.3 | 5.6 | 5.5 | 5.3 | 5.2 | 5.0 |
| 2.5 | 3.41 | 3.34 | 7.0 | 6.2 | 6.0 | 5.8 | 5.7 | 6.1 | 5.9 | 5.8 | 5.6 | 5.9 | 5.8 | 5.7 | 5.5 | 5.8 | 5.6 | 5.5 | 5.4 | 5.3 |
| 3 | 3.99 | 3.9 | 10.0 | 6.3 | 6.1 | 6.0 | 5.9 | 6.2 | 6.1 | 6.0 | 5.9 | 6.0 | 5.9 | 5.8 | 5.7 | 5.9 | 5.8 | 5.7 | 5.6 | 5.5 |

