

屋内照明器具特性	
品番 (品名)	HH- CB1212NH
光源	LED5000_70_5200 x1 5200.0lm
管理番号	K0142411(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																							
		床	10%				10%				10%				10%				0%																																							
上方光束	8%	室指数																			照明率 (X0.01)																			ZCM																		
下方光束	92%																																																									
保守率	良 中 否	0.63	0.6	0.6	0.56	0.6	54	42	34	29	53	41	34	28	49	39	33	28	47	38	32	27	25																																			
		0.6	0.6	0.6	0.6	0.8	64	52	44	38	62	51	44	38	58	49	42	37	55	47	41	36	33																																			
		0.56	0.56	0.56	0.56	1.0	71	60	52	46	68	58	51	45	64	56	49	44	61	53	48	43	40																																			
		0.56	0.56	0.56	0.56	1.25	76	66	59	53	74	65	58	52	70	62	56	51	66	59	54	50	46																																			
下方投影面積	c m <sup>2</sup>	1.5	1.5	1.5	1.5	81	71	64	58	78	70	63	58	74	67	61	56	70	64	59	55	51																																				
		2.0	2.0	2.0	2.0	86	78	72	67	84	77	71	66	79	73	68	64	75	70	66	62	58																																				
取付高さ	器具間隔最大限		H m	1.29H m	1.29H m	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5																																				
	横方向 (A)	縦方向 (B)				3.0	92	86	81	77	90	84	80	75	85	81	77	73	81	77	74	71	66																																			
H m	1.29H m	1.29H m	H m	1.29H m	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0																																				
					5.0	98	93	90	86	95	91	88	85	91	88	85	82	87	84	82	79	75																																				
					7.0	100	97	94	91	98	95	92	90	93	91	89	87	89	87	85	84	79	75																																			
					10.0	102	99	97	95	100	97	95	93	95	93	92	90	91	90	88	87	82	78																																			

