

# 屋内照明器具特性

品番 (品名) **LGB16159**

光源 **LLD3020CU1 ×1** **615.0 lm**

管理番号 **K0190103 (1) DR1**

BZ分類 **BZ1**

器具効率	89%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁																	
下方光束	89%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	77	72	69	67	76	72	69	67	75	71	69	67	74	71	69	67	66	
	中 0.63	0.8	82	78	75	73	81	77	74	73	80	76	74	72	79	76	74	72	71	
	否 0.56	1.0	85	81	78	76	84	80	78	76	83	80	77	76	81	79	77	75	74	
下方投影面積	cm <sup>2</sup>	1.25	87	84	81	79	86	83	81	79	85	82	80	79	83	81	80	78	77	
		1.5	88	86	83	82	88	85	83	81	86	84	82	81	85	83	81	80	79	
等価発光面積	cm <sup>2</sup>	2.0	90	88	86	85	90	87	86	84	88	86	85	83	86	85	84	83	81	
		2.5	92	90	88	87	91	89	87	86	89	88	86	85	87	86	85	84	83	
取付高さ	器具間隔最大限		3.0	92	91	89	88	91	90	89	87	90	88	87	86	88	87	86	85	84
	横方向 (A)	縦方向 (B)	4.0	93	92	91	90	92	91	90	89	91	90	89	88	89	88	87	87	85
Hm	0.34Hm	0.34Hm	5.0	94	93	92	91	93	92	91	90	91	90	90	89	89	89	88	88	86
			7.0	95	94	93	92	94	93	92	92	92	91	91	90	90	90	89	89	87
			10.0	95	94	94	94	94	94	93	93	92	92	91	91	90	90	90	90	87

