

# 屋内照明器具特性

品番 (品名)	XND9985S WZ																
光源	LED4000_80_12795 ×1 12795.0 1m																
管理番号	K0188510(0)DB1																
BZ分類	BZ1																

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床	10%				10%				10%				10%				0%
下方光束	100%		室指数	照明率 ( X0.01) ZCM																
保守率	良 中 否	0.76	0.6	75	67	62	58	74	67	62	58	73	66	61	58	71	65	61	58	57
		0.72	0.8	84	77	72	69	83	77	72	69	81	76	72	69	80	75	71	68	67
			1.0	89	83	79	76	88	83	79	75	86	82	78	75	85	81	77	75	73
		0.64	1.25	94	88	84	81	92	88	84	81	90	86	83	81	89	85	82	80	78
下方投影面積	c m <sup>2</sup>	1.5	96	91	88	85	95	91	87	85	93	89	86	84	91	88	86	83	82	
		2.0	99	96	93	90	98	95	92	90	96	93	91	89	94	92	90	88	86	
取付高さ	器具間隔最大限		2.5	101	98	96	93	100	97	95	93	98	96	94	92	96	94	92	91	89
	横方向 (A)	縦方向 (B)	3.0	103	100	98	96	101	99	97	95	99	97	95	94	97	96	94	93	91
H m	1.32 H m	1.32 H m	4.0	104	102	100	99	103	101	99	98	101	99	98	96	99	97	96	95	93
			5.0	105	103	102	100	104	102	101	100	102	100	99	98	100	99	98	97	94
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	98	96
			10.0	107	106	105	104	106	105	104	103	103	103	102	102	101	101	100	100	97

